


BRILUMEN DATA SHEET

ECO-SERIE . 230V

230V LED Strip SMD5050 . IP65 . 50M/Reel . 60 LED/M
Fita LED 230V SMD5050 . IP65 . 50M/Rolo . 60 LED/M



PRODUCT CODE	NOMINAL POWER	POWER CONSUMPTION	CRI	CCT	RATED LUMINOUS FLUX/METER	LED EFFICACY
2002-127.03	14,4 W/m	7,4 W/m	> 75	2800K	548 lm/m	74 lm/W
2002-127.02	14,4 W/m	7,4 W/m	> 75	4200K	585 lm/m	79 lm/W
2002-127.01	14,4 W/m	7,4 W/m	> 75	6400K	607 lm/m	82 lm/W



8013-0030



8013-0031



8013-0032



8013-0033

PRODUCT CODE	DESCRIPTION
8013-0030	Power cord . Retificador
8013-0031	Connector . Conetor
8013-0032	End cap . Terminal
8013-0033	Clip . Braçadeira

WARNING . ADVERTÊNCIA

EN

- Do not connect the 230V led strip without a rectifier.
- Always place a terminal at the end of the strip. Otherwise it may result in damage to the material or danger to people or animals.
- Don't install in exiguous, closed, less ventilated places or directly exposed to sunlight.
- This product is not suitable to be used more than a continuous period of 6 hours per day. Contact us for further informations.
- Test the product before installing or cutting the strip.
- There could be some variations on the colour temperature between different rolls.
- We will only accept product returns if the product returned is in perfect selling conditions.
- Warranty for defected manufacturing can not be required after installing the product if the defect can be detected before the installation.
- Maximum length for continuous connection is 50 meters.
- To cut the 230V led strip into different parts, the cut has to be made in the middle of the specific space and not on the edges, otherwise it can result in irreversible damages to the product (see instructions on label).
- Disrespecting this rules results in warranty loss against manufacturing defects.

PT

- Não ligar a fita LED 230V sem o retificador.
- Colocar sempre um terminal no fim da fita. A sua falta poderá resultar em danos do material ou resultar em perigo para as pessoas ou animais.
- Não instalar em locais exíguos, fechados, pouco ventilados ou expostos à luz solar direta.
- Produto não adequado para a utilização superior a 6 horas contínuas diárias. Contacte-nos para aconselhamento.
- Teste o produto antes de instalar ou cortar.
- Pode existir ligeiras variações na temperatura da cor entre vários rolos.
- Apenas aceitaremos devoluções se o produto nos for devolvido em perfeitas condições de comercialização.
- A garantia sobre defeitos de fabrico deste produto não poderá ser reclamada, após a instalação, se o defeito poder ser detetado antes da sua instalação.
- Comprimento máximo de ligação contínua 50 metros.
- Para cortar a fita LED 230V, o corte deverá ser feito no centro do espaço para esse efeito. Se o corte for efetuado nas extremidades desse espaço o produto poderá ficar com danos irreversíveis (ver instruções).
- O desrespeito destas regras resulta na perda de garantia contra defeitos de fabrico.