

DESCRIPTION

Technical lighting is increasingly considered in the planning of spaces and their purpose because every location has its own specific lighting requirements.


Therefore, we would like to introduce you to the ORIS 50mm on Track for a universal 230V track application, which promises to innovate and complement technical lighting solutions.

MOUNTING TYPE	Uni Track
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Anodized aluminium, Textured Black, Textured White
CONTROL	CASAMBI, DALI / Switch Dim, ON/OFF


LED FEATURES

LUMINOUS EFFICIENCY	UP TO 167 lm/W
CRI	CRI→90
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

TECHNICAL DRAWING

ICONOGRAPHY

**ORIS 50 OPAL 230V
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90**

LENGTH	POWER	FINISHING	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
850	20	AL, TB, TW	CS, DA, NF	90	3217	2348	3000K	5225XX.0809.930.FI
850	20	AL, TB, TW	CS, DA, NF	90	3337	2436	4000K	5225XX.0809.940.FI
1130	26.6	AL, TB, TW	CS, DA, NF	90	4289	3131	3000K	5225XX.1109.930.FI
1130	26.6	AL, TB, TW	CS, DA, NF	90	4449	3248	4000K	5225XX.1109.940.FI
1410	33.3	AL, TB, TW	CS, DA, NF	90	5361	3914	3000K	5225XX.1409.930.FI
1410	33.3	AL, TB, TW	CS, DA, NF	90	5561	4060	4000K	5225XX.1409.940.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	FINISHING	FI	BEAM ANGLE	BA
CASAMBI	CS	Anodized aluminium	AL	90°	90
DALI / Switch Dim	DA	Textured Black	TB		
ON/OFF	NF	Textured White	TW		

ACCESSORIES

	Track ON/OFF Susp./Surf. ON/OFF Track 1m White UP1459102-1 ON/OFF Track 2m White UP1459102 SEM DescAbr - UP1459429 UP1459429 SEM DescAbr - UP1459429-1 UP1459429-1
	Track DALI Susp./Surf. DALI Track 1m White UP1459107-1 DALI Track 2m White UP1459107 SEM DescAbr - UP1459439 UP1459439 SEM DescAbr - UP1459439-1 UP1459439-1
	Recess. Track ON/OFF ON/OFF Rec. Track 1m BL UP1459312-1 ON/OFF Rec. Track 1m WH UP1459112-1 ON/OFF Rec. Track 2m BL UP1459312 ON/OFF Rec. Track 2m WH UP1459112
	Recessed Track DALI DALI Rec. Track 1m BL UP1459317-1 DALI Rec. Track 1m WH UP1459117-1 DALI Rec. Track 2m BL UP1459317 DALI Rec. Track 2m WH UP1459117