

DESCRIPTION

Light downward. Function with elegance.

Staying true to the visual language of the ARIC collection - elegant luminous rings with compact dimensions - ARIC DOWN features a downward light emission.


This version is designed for spaces that require direct lighting without compromising on visual comfort or formal elegance.

Perfect for hospitality areas, retail environments, or circulation zones that benefit from a flexible and architecturally integrated lighting solution.

MOUNTING TYPE	Suspension
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Textured Black, Textured Silver, Textured White
CONTROL	CASAMBI, DALI / Switch Dim, ON/OFF



TECHNICAL DRAWING



LED FEATURES

LUMINOUS EFFICIENCY	UP TO 135 lm/W
CRI	CRI→90
LIFESPAN	72000h Tp55
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/F10
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY



ARIC DOWN CRI→90
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - OPAL

DIAMETER	POWER	FINISHING	COLOR TEMP.	CONTROL TYPE	LED LUMENS	LUMINAIRE LM	CODE
600	26.6	TB, TS, TW	2700K	CS, DA, NF	3249	2274	127XX.0609.9CT.FI
600	26.6	TB, TS, TW	3000K	CS, DA, NF	3435	2405	127XX.0609.9CT.FI
600	26.6	TB, TS, TW	4000K	CS, DA, NF	3596	2517	127XX.0609.9CT.FI
900	40.3	TB, TS, TW	2700K	CS, DA, NF	4917	3442	127XX.0909.9CT.FI
900	40.3	TB, TS, TW	3000K	CS, DA, NF	5200	3640	127XX.0909.9CT.FI
900	40.3	TB, TS, TW	4000K	CS, DA, NF	5443	3810	127XX.0909.9CT.FI
1200	54	TB, TS, TW	2700K	CS, DA, NF	6585	4610	127XX.1209.9CT.FI
1200	54	TB, TS, TW	3000K	CS, DA, NF	6964	4875	127XX.1209.9CT.FI
1200	54	TB, TS, TW	4000K	CS, DA, NF	7290	5103	127XX.1209.9CT.FI
1500	67.7	TB, TS, TW	2700K	CS, DA, NF	8253	5777	127XX.1509.9CT.FI
1500	67.7	TB, TS, TW	3000K	CS, DA, NF	8728	6110	127XX.1509.9CT.FI
1500	67.7	TB, TS, TW	4000K	CS, DA, NF	9137	6396	127XX.1509.9CT.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	COLOR TEMP.	CT	FINISHING	FI
CASAMBI	CS	2700K	27	Textured Black	TB
DALI / Switch Dim	DA	3000K	30	Textured Silver	TS
ON/OFF	NF	4000K	40	Textured White	TW


ACCESSORIES

	Suspension Kit	Silver
	Suspension kit 1,5m (1un)	80303017.SL
	Suspension kit 3 m (1un)	80303018.SL
	Suspension kit 5 m (1un)	80303019.SL
	Recessed power box 200mm	120mm
	Textured Black	50041023.TB
	Textured Silver	50041023.TS
	Textured white	50041023.TW
	Surface ceiling box 200mm	200mm



200mm surface box TB
200mm surface box TS
200mm surface box TW

50041027.TB
50041027.TS
50041027.TW



Surface ceiling box 360mm
360mm surface box TB
360mm surface box TS
360mm surface box TW

360mm
50041030.TB
50041030.TS
50041030.TW



Power Cable Iris
Power Cable 3m
Power Cable 5m
Power Cable Iris 1,5m
Power Cable Iris 1m

Universal
80303041
80303042
80303040
2080-042