

**DESCRIPTION**

Light inward. Immersive atmosphere.

With its compact circular body and sophisticated design, ARIC IN embodies the balance between pure geometry and luminous expression.


In this version, light is emitted inward toward the center of the ring, creating a soft, immersive, and theatrical effect. The indirect illumination enhances the central space, offering a sense of depth and warmth - ideal for settings that call for a more emotional or decorative lighting.

The perfect solution for suspended applications in reception areas, waiting rooms, galleries, or any space where light is meant to complement the architecture with subtlety.

<b>MOUNTING</b>	Suspension
<b>LIGHT DISTRIBUTION</b>	Direct
<b>POWER SUPPLY</b>	220-230V / 50-60 Hz
<b>WARRANTY</b>	5 Years
<b>FINISHING</b>	Textured Black, Textured Silver, Textured White
<b>CONTROL</b>	CASAMBI, DALI / PUSH Dim, ON/OFF



**TECHNICAL DRAWING**



**LED FEATURES**

<b>LUMINOUS EFFICIENCY</b>	UP TO 135 lm/W
<b>CRI</b>	CRI→90
<b>LIFESPAN</b>	72000h Tp55
<b>STEPS MACADAM</b>	3 Steps MacAdam
<b>LUMEN MAINTENANCE</b>	L90/F10
<b>PHOTOBIOLOGICAL RISK</b>	RG1

**ICONOGRAPHY**



**ARIC IN CRI→90  
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - OPAL**

DIAMETER	POWER	FINISHING	COLOR TEMP.	CONTROLTYPE	LED LUMENS	LUMINAIRE LM	CODE
600	26,6	TB, TS, TW	2700K	CS, DA, NF	3249	2274	125XX.0609.9CT.FI
600	26,6	TB, TS, TW	3000K	CS, DA, NF	3435	2405	125XX.0609.9CT.FI
600	26,6	TB, TS, TW	4000K	CS, DA, NF	3596	2517	125XX.0609.9CT.FI
900	40,3	TB, TS, TW	2700K	CS, DA, NF	4917	3442	125XX.0909.9CT.FI
900	40,3	TB, TS, TW	3000K	CS, DA, NF	5200	3640	125XX.0909.9CT.FI
900	40,3	TB, TS, TW	4000K	CS, DA, NF	5443	3810	125XX.0909.9CT.FI
1200	54	TB, TS, TW	2700K	CS, DA, NF	6585	4610	125XX.1209.9CT.FI
1200	54	TB, TS, TW	3000K	CS, DA, NF	6964	4875	125XX.1209.9CT.FI
1200	54	TB, TS, TW	4000K	CS, DA, NF	7290	5103	125XX.1209.9CT.FI
1500	67,7	TB, TS, TW	2700K	CS, DA, NF	8253	5777	125XX.1509.9CT.FI
1500	67,7	TB, TS, TW	3000K	CS, DA, NF	8728	6110	125XX.1509.9CT.FI
1500	67,7	TB, TS, TW	4000K	CS, DA, NF	9137	6396	125XX.1509.9CT.FI

**SELECT YOUR PREFERRED OPTION**

CONTROLTYPE	XX	COLOR TEMP.	CT	FINISHING	FI
CASAMBI	CS	2700K	27	Textured Black	TB
DALI / PUSH Dim	DA	3000K	30	Textured Silver	TS
ON/OFF	NF	4000K	40	Textured White	TW


**ACCESSORIES**

	<b>Suspension Kit</b>	Silver
	Suspension kit 1,5m (1un)	80303017.SL
	Suspension kit 3 m (1un)	80303018.SL
	Suspension kit 5 m (1un)	80303019.SL
	<b>Recessed power box 200mm</b>	120mm
	Textured Black	50041023.TB
	Textured Silver	50041023.TS
	Textured white	50041023.TW



Surface ceiling box 200mm  
200mm surface box TB  
200mm surface box TS  
200mm surface box TW

200mm  
50041027.TB  
50041027.TS  
50041027.TW



Surface ceiling box 360mm  
360mm surface box TB  
360mm surface box TS  
360mm surface box TW

360mm  
50041030.TB  
50041030.TS  
50041030.TW



Power Cable Iris  
Power Cable 3m  
Power Cable 5m  
Power Cable Iris 1,5m  
Power Cable Iris 1m

Universal  
80303041  
80303042  
80303040  
2080-042