

DESCRIPTION

Light outward. Subtle emphasis.

The ARIC range offers a striking architectural presence while maintaining a discreet visual integration. ARIC OUT embodies this philosophy through outward-directed light emission, creating a soft and elegant halo around the ring.


This interplay of light and shadow enhances the surrounding architectural structure, contributing to a visually impactful yet lightweight atmosphere.

Ideal for large spaces such as lobbies, conference rooms, or entrances, where visual effect takes center stage without relying on excessive volume.

MOUNTING TYPE	Suspension
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Textured Black, Textured Silver, Textured White
CONTROL	CASAMBI, DALI / Switch Dim, ON/OFF



TECHNICAL DRAWING



LED FEATURES

LUMINOUS EFFICIENCY	UP TO 135 lm/W
CRI	CRI→90
LIFESPAN	72000h Tp55
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/F10
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY



**ARIC OUT CRI→90
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - OPAL**

DIAMETER	POWER	FINISHING	COLOR TEMP.	CONTROL TYPE	LED LUMENS	LUMINAIRE LM	CODE
600	24.5	TB, TS, TW	2700K	CS, DA, NF	2985	2090	126XX.0609.9CT.FI
600	24.5	TB, TS, TW	3000K	CS, DA, NF	3157	2210	126XX.0609.9CT.FI
600	24.5	TB, TS, TW	4000K	CS, DA, NF	3305	2313	126XX.0609.9CT.FI
900	38.2	TB, TS, TW	2700K	CS, DA, NF	4653	3257	126XX.0909.9CT.FI
900	38.2	TB, TS, TW	3000K	CS, DA, NF	4921	3445	126XX.0909.9CT.FI
900	38.2	TB, TS, TW	4000K	CS, DA, NF	5152	3606	126XX.0909.9CT.FI
1200	51.8	TB, TS, TW	2700K	CS, DA, NF	6322	4425	126XX.1209.9CT.FI
1200	51.8	TB, TS, TW	3000K	CS, DA, NF	6685	4680	126XX.1209.9CT.FI
1200	51.8	TB, TS, TW	4000K	CS, DA, NF	6998	4899	126XX.1209.9CT.FI
1500	65.5	TB, TS, TW	2700K	CS, DA, NF	7990	5593	126XX.1509.9CT.FI
1500	65.5	TB, TS, TW	3000K	CS, DA, NF	8449	5915	126XX.1509.9CT.FI
1500	65.5	TB, TS, TW	4000K	CS, DA, NF	8845	6192	126XX.1509.9CT.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	COLOR TEMP.	CT	FINISHING	FI
CASAMBI	CS	2700K	27	Textured Black	TB
DALI / Switch Dim	DA	3000K	30	Textured Silver	TS
ON/OFF	NF	4000K	40	Textured White	TW

ACCESSORIES

	Suspension Kit	Silver
	Suspension kit 1,5m (1un)	80303017.SL
	Suspension kit 3 m (1un)	80303018.SL
	Suspension kit 5 m (1un)	80303019.SL
	Recessed power box 200mm	120mm
	Textured Black	50041023.TB
	Textured Silver	50041023.TS
	Textured white	50041023.TW



Surface ceiling box 200mm
200mm surface box TB
200mm surface box TS
200mm surface box TW

200mm
50041027.TB
50041027.TS
50041027.TW



Surface ceiling box 360mm
360mm surface box TB
360mm surface box TS
360mm surface box TW

360mm
50041030.TB
50041030.TS
50041030.TW



Power Cable Iris
Power Cable 3m
Power Cable 5m
Power Cable Iris 1,5m
Power Cable Iris 1m

Universal
80303041
80303042
80303040
2080-042