

DESCRIPTION

The range of CAROLINE luminaires, with models that go from 10W to 30W, has a CRI higher than 80, respecting the objects' original colours. With a white finish and an easy and quick mounting way, CAROLINE range is presented as a quality solution when replacing downlights with traditional light sources or already outdated LED technology.


MOUNTING	Encastrar
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	White
CONTROL	CASAMBI, DALI / PUSH Dim, ON/OFF




LED FEATURES

LUMINOUS EFFICIENCY	UP TO 120 lm/W
CRI	CRI->80
LIFESPAN	40.000 Hours Tp 55°
STEPS MACADAM	4 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

TECHNICAL DRAWING



ICONOGRAPHY



CAROLINE 10W - 120MM
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI->80

LENGTH	POWER	FINISHING	CONTROLTYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
120	10	WH	CS, DA, NF	60, 90	1146	1060	3000K	5375XX.10.12.60.830
120	10	WH	CS, DA, NF	60, 90	1146	1060	3000K	5375XX.10.12.90.830
120	10	WH	CS, DA, NF	60, 90	1146	1060	3000K	5375XX.10.12.BA.830
120	10	WH	CS, DA, NF	60, 90	1200	1110	4000K	5375XX.10.12.60.840
120	10	WH	CS, DA, NF	60, 90	1200	1110	4000K	5375XX.10.12.90.840
120	10	WH	CS, DA, NF	60, 90	1200	1110	4000K	5375XX.10.12.BA.840

SELECT YOUR PREFERRED OPTION

CONTROLTYPE	XX	FINISHING	FI	BEAM ANGLE	BA
CASAMBI	CS	White	WH	60°	60
DALI / PUSH Dim	DA			90°	90
ON/OFF	NF				