

DESCRIPTION

The new range of CAROLINE luminaires, with models that go from 10W to 30W, has a CRI higher than 80, respecting the objects original colours. With a white finish and an easy and quick mounting way, CAROLINE range is presented as a quality solution when replacing downlights with traditional light sources or already outdated LED technology. Depending on the wattage, these light fittings may have between 1.200 and 3.438 lumens and a 60° or 90° beam angle, technical features suitable for lighting commercial spaces, such as apparel stores, art galleries, libraries, restaurants, coffee shops, supermarkets, etc. These luminaires are available in colour temperatures 3000K and 4000K, are compatible with emergency kit and have a 5 Year Warranty.


MOUNTING TYPE Recessed LIGHT DISTRIBUTION Direct

POWER SUPPLY 220-230V / 50-60 Hz

WARRANTY 5 Years FINISHING White ON/OFF CONTROL



TECHNICAL DRAWING





LED FEATURES

UP TO 112 lm/W **LUMINOUS EFFICIENCY** CRI→80 CRI 50.000 Hours LIFESPAN STEPS MACADAM 4 Steps MacAdam **LUMEN MAINTENANCE** L70/B50 PHOTOBIOLOGICAL RISK RG1

ICONOGRAPHY

























| CHI-00 | | | | | | | | | | | | |
|--------|-----|----|-----------|--------------|------------|------------|--------------|-------------|-----------------|--|--|--|
| | | | FINISHING | CONTROL TYPE | BEAM ANGLE | LED LUMENS | LUMINAIRE LM | COLOR TEMP. | | | | |
| | 170 | 10 | WH | NF | 60, 90 | 1189 | 1100 | 3000K | 375.15.25.BA.30 | | | |
| | 170 | 10 | WH | NF | AN 9N | 1211 | 1120 | YUUUK | 375 15 25 BA 40 | | | |

| SELECT YOUR PREFERRED | CONTROL TYPE | XX | FINISHING | FI | BEAM ANGLE | BA |
|-----------------------|--------------|----|-----------|----|------------|----|
| OPTION | ON/OFF | NF | White | WH | 60° | 60 |
| | | | | | 90° | 90 |