

#### **DESCRIPTION**

The new range of CAROLINE luminaires, with models that go from 10W to 30W, has a CRI higher than 80, respecting the objects original colours. With a white finish and an easy and quick mounting way, CAROLINE range is presented as a quality solution when replacing downlights with traditional light sources or already outdated LED technology. Depending on the wattage, these light fittings may have between 1.200 and 3.438 lumens and a 60° or 90° beam angle, technical features suitable for lighting commercial spaces, such as apparel stores, art galleries, libraries, restaurants, coffee shops, supermarkets, etc. These luminaires are available in colour temperatures 3000K and 4000K, are compatible with emergency kit and have a 5 Year Warranty.


MOUNTING TYPE Recessed LIGHT DISTRIBUTION Direct

POWER SUPPLY 220-230V / 50-60 Hz

WARRANTY 5 Years FINISHING White ON/OFF CONTROL



# TECHNICAL DRAWING





#### **LED FEATURES**

UP TO 111 lm/W **LUMINOUS EFFICIENCY** CRI CRI→80 LIFESPAN 50.000 Hours STEPS MACADAM 4 Steps MacAdam **LUMEN MAINTENANCE** L70/B50 PHOTOBIOLOGICAL RISK RG1

### ICONOGRAPHY























## CAROLINE 20W - 145MM PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80

									CODE			
	170	20	WH	NF	60, 90	2303	2130	3000K	375.15.53.BA.30			
	170	20	WH	NF	60, 90	2389	2210	4000K	375.15.53.BA.40			

SELECT YOUR PREFERRED	CONTROL TYPE	XX	FINISHING	FI	BEAM ANGLE	BA
OPTION	ON/OFF	NF	White	WH	60°	60
	•				900	90