. brilumen

DESCRIPTION

The new range of CAROLINE luminaires, with models that go from 10W to 30W, has a CRI higher than 80, respecting the objects original colours. With a white finish and an easy and quick mounting way, CAROLINE range is presented as a quality solution when replacing downlights with traditional light sources or already outdated LED technology. Depending on the wattage, these light fittings may have between 1.200 and 3.438 lumens and a 60° or 90° beam angle, technical features suitable for lighting commercial spaces, such as apparel stores, art galleries, libraries, restaurants, coffee shops, supermarkets, etc. These luminaires are available in colour temperatures 3000K and 4000K, are compatible with emergency kit and have a 5 Year Warranty.

MOUNTING TYPE LIGHT DISTRIBUTION POWER SUPPLY WARRANTY FINISHING CONTROL Recessed Direct 220-230V / 50-60 Hz 5 Years White 0N/0FF

LED FEATURES

LUMINOUS EFFICIENCY CRI LIFESPAN STEPS MACADAM LUMEN MAINTENANCE PHOTOBIOLOGICAL RISK UP TO 106 lm/W CRI→80 50.000 Hours 4 Steps MacAdam L70/B50 RG1

ICONOGRAPHY



145





CAROLINE 30W - 190MM
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80

CRI>80 PRODU	JCT TABLE AND TE	CHNICAL SPECIFI	CATIONS - CRI \rightarrow 80					
LENGTH	POWER	FINISHING	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
225	30	WH	NF	60, 90	3319	3070	3000K	375.20.79.BA.30
225	30	WH	NF	60, 90	3438	3180	4000K	375.20.79.BA.40
	SEI	SELECT YOUR PREFERRED		CONTROL TYPE	XX	FINISHING	FI BEAM /	ANGLE BA
	OPTION			0N/0FF	NF	White V	WH 60	0° 60
							90	0° 90

1