

## DESCRIPTION

**NOTE:** The price listed below is for 1 meter.  
 The item is sold in 5 meters reel, so the minimum order is 5 meters.  
 Please insert 5 units into the shopping cart, or multiples of this value.

Brilumen's Professional LED Strip is the brand's star and it stands out for its reliability, versatility and light quality, being considered the best LED strip on the market. With different wattages, luminous fluxes and widths, this 24V LED strip is available in the colour temperature from 2500K to 6500K, can have 30, 60, 120, 160 and 280 LED and a CRI higher than 80. Due to the double-sided adhesive tape on the back, this product, besides being quite flexible, is easy to install and, depending on the model, is available with IP20 or IP67. To extend its operating cycle, it is recommended to install this LED strip in the right aluminium profile. When used properly, this high-quality LED strip for professional use, can be turned on 24 hours a day for 3 years without losing its features, and is highly recommended in numerous projects such as hotels, restaurants, shops, residences, etc. If the goal is to install a reliable, quality and easy to install product, Brilumen's Professional LED strip is undoubtedly the perfect choice.


**POWER SUPPLY** 24V / 50-60 Hz

## LED FEATURES

## ICONOGRAPHY



## TECHNICAL DRAWING



## 2002-142 14,4W IP65

### PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - EFFICIENCY SMD2835 14,4W 60 LED IP65

POWER	VOLTAGE	COLOR TEMP.	RATED LUMINOUS FLUX/M	LED EFFICIENCY	UN.	CODE
14.4	24V	2700K	1253	87	5MT	2002-142.80.27
14.4	24V	4200K	1296	90	5MT	2002-142.80.42
14.4	24V	6500K	1368	95	5MT	2002-142.80.65

## ACCESSORIES



**Trix aluminium profile**  
**Trix aluminium profile** 8010-2002.AL



**IP20 LED Strip Connector**  
**IP20 LED Strip Connector** 8013-0014



**Connector w/ binder 15cm**  
**Connector w/ binder 15cm** 8013-0015



**Double c/t w/ binder**  
**Double c/t w/ binder** 8013-0016



**L connector**  
**L connector** 8013-0017



**12,5 mm Connector**  
**12,5 mm Connector** 8013-0026



FP02 Edging Tile Profile	SEM TITULO -
FP02 Edging Tile Profile	G810-2034



OP23 Corner Profile	SEM TITULO -
OP23 Corner Profile	G810-4052



LP05 aluminium profile	SEM TITULO -
LP05 aluminium profile	G810-5201



LP03 Recessed Profile	SEM TITULO -
LP03 Recessed Profile	G810-6032



NP17 aluminium profile	SEM TITULO -
NP17 aluminium profile	G810-2026



OP15 aluminium profile	SEM TITULO -
OP15 aluminium profile	G810-2062



LP06 aluminium profile	SEM TITULO -
LP06 aluminium profile	G810-6062



LP08 Recessed Profile	SEM TITULO -
LP08 Recessed Profile	G810-6082



LP10 aluminium profile	SEM TITULO -
LP10 aluminium profile	G810-7012



NP04 aluminium profile	SEM TITULO -
NP04 aluminium profile	G820-1012



NP06 aluminium profile	SEM TITULO -
NP06 aluminium profile	G830-1017



NP07 Recessed Profile	SEM TITULO -
NP07 Recessed Profile	G830-5015