

# DESCRIPTION

The growing need to find a powerful and versatile luminaire that can serve as a floodlight or as an industrial light fitting, led Brilumen to present an efficient solution that meets these two requirements, the ELLINGTON product range. These floodlights can light up building facades, as they have an IP65, ingress protection rating suitable for outdoor areas, and can be installed on the floor or the wall.


MOUNTING TYPE LIGHT DISTRIBUTION Surface Direct 220-230V / 50-60 Hz **POWER SUPPLY** WARRANTY 5 Years CONTROL 1-10V, DALI, ON/OFF




#### LED FEATURES

UP TO 175 lm/W **LUMINOUS EFFICIENCY** CRI→80 LIFESPAN 50.000 Hours STEPS MACADAM 4 Steps MacAdam LUMEN MAINTENANCE L90/B50 PHOTOBIOLOGICAL RISK RG1

#### **TECHNICAL DRAWING**



### ICONOGRAPHY





## **ELLINGTON 120W**

PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80



SELECT YOUR PREFERRED	CONTROL TYPE	XX	BEAM ANGLE	ВА
OPTION	1-10V	1V	60°	60
	DALI	DL	90°	90
	ON/OFF	NF		