

DESCRIPTION


The growing need to find a powerful and versatile luminaire that can serve as a floodlight or as an industrial light fitting, led Brilumen to present an efficient solution that meets these two requirements, the ELLINGTON product range. These floodlights can light up building facades, as they have an IP65, ingress protection rating suitable for outdoor areas, and can be installed on the floor or the wall.

MOUNTING TYPE	Surface
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
CONTROL	1-10V, DALI, ON/OFF

LED FEATURES

LUMINOUS EFFICIENCY	UP TO 175 lm/W
CRI	CRI>80
LIFESPAN	50.000 Hours
STEPS MACADAM	4 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY



ELLINGTON 160W PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI>80

LENGTH	POWER	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
355	160	1V, DL, NF	60, 90	22400	21280	6500K	491XX.BA.865
355	160	1V, DL, NF	60, 90	28000	26600	4000K	491XX.BA.840

SELECT YOUR PREFERRED
OPTION

CONTROL TYPE	XX
1-10V	1V
DALI	DL
ON/OFF	NF

BEAM ANGLE	BA
60°	60
90°	90



TECHNICAL DRAWING

