

# DESCRIPTION

The growing need to find a powerful and versatile luminaire that can serve as a floodlight or as an industrial light fitting, led Brilumen to present an efficient solution that meets these two requirements, the ELLINGTON product range. These floodlights can light up building facades, as they have an IP65, ingress protection rating suitable for outdoor areas, and can be installed on the floor or the wall.


MOUNTING TYPE LIGHT DISTRIBUTION Surface Direct 220-230V / 50-60 Hz **POWER SUPPLY** WARRANTY 5 Years CONTROL 1-10V, DALI, ON/OFF

# 000000 999999 156666 155666


# LED FEATURES

UP TO 175 lm/W **LUMINOUS EFFICIENCY** CRI→80 LIFESPAN 50.000 Hours STEPS MACADAM 4 Steps MacAdam LUMEN MAINTENANCE L90/B50 PHOTOBIOLOGICAL RISK RG1

### **TECHNICAL DRAWING**



# ICONOGRAPHY





#### **ELLINGTON 160W** PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80

LENGTH	POWER	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
355	160	1V, DL, NF	60, 90	22400	21280	6500K	491XX.BA.865
355	160	1V, DL, NF	60, 90	28000	26600	4000K	491XX.BA.840

SELECT YOUR PREFERRED	CONTROL TYPE	XX	BEAM ANGLE	ВА
OPTION	1-10V	1V	60°	60
	DALI	DL	90°	90
	ON/OFF	NF		