

## DESCRIPTION


The growing need to find a powerful and versatile luminaire that can serve as a floodlight or as an industrial light fitting, led Brilumen to present an efficient solution that meets these two requirements, the ELLINGTON product range. These floodlights can light up building facades, as they have an IP66, ingress protection rating suitable for outdoor areas, and can be installed on the floor or the wall.

MOUNTING TYPE	Surface
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
CONTROL	1-10V, DALI, ON/OFF

## LED FEATURES

LUMINOUS EFFICIENCY	UP TO 175 lm/W
CRI	CRI>80
LIFESPAN	50.000 Hours
STEPS MACADAM	4 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

## ICONOGRAPHY



## ELLINGTON 40W PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI>80

POWER	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
40	1V, DL, NF	60, 90	5600	5320	6500K	488XX.BA.865
40	1V, DL, NF	60, 90	7000	6650	4000K	488XX.BA.840

SELECT YOUR PREFERRED  
OPTION

CONTROL TYPE	XX
1-10V	1V
DALI	DL
ON/OFF	NF

BEAM ANGLE	BA
60°	60
90°	90



## TECHNICAL DRAWING

