

DESCRIPTION

A circle is the reflection of eternity; it has no beginning and no end. Backed by a 5-year warranty, the OLYMPIA and HELIUS luminaires were designed and inspired to provide high-quality ambient lighting. With a built-in driver available in various wattages, diameters, and mounting options, these circular profiles can be easily installed in a wide range of spaces, such as shops, museums, galleries, hotels, restaurants, offices, meeting rooms, or waiting areas, among others.

OPAL: UGR<22

Microprismatic: UGR<19

|                    |   |
|--------------------|---|
| MOUNTING TYPE      | Suspension                                      |
| LIGHT DISTRIBUTION | Direct  |
| POWER SUPPLY       | 220-230V / 50-60 Hz                             |
| WARRANTY           | 5 Years   |
| FINISHING          | Textured Black, Textured Silver, Textured White |
| CONTROL            | CASAMBI, DALI / Switch Dim, ON/OFF              |


LED FEATURES

|                      |                 |
|----------------------|-----------------|
| LUMINOUS EFFICIENCY  | UP TO 172 lm/W  |
| CRI                  | CRI→90          |
| LIFESPAN             | 72000h Tp55     |
| STEPS MACADAM        | 3 Steps MacAdam |
| LUMEN MAINTENANCE    | L90/F10         |
| PHOTOBIOLOGICAL RISK | RG0             |

ICONOGRAPHY



TECHNICAL DRAWING



HELIUS SUSPENDED CRI→90  
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - OPAL

| DIAMETER | POWER | FINISHING  | COLOR TEMP. | CONTROL TYPE | LED LUMENS | LUMINAIRE LM | CODE               |
|----------|-------|------------|-------------|--------------|------------|--------------|--------------------|
| 400      | 17.3  | TB, TS, TW | 3000K       | CS, DA, NF   | 2751       | 1925         | 5230XX.0409.9CT.FI |
| 400      | 17.3  | TB, TS, TW | 4000K       | CS, DA, NF   | 2906       | 2034         | 5230XX.0409.9CT.FI |
| 400      | 24.4  | TB, TS, TW | 3000K       | CS, DA, NF   | 3811       | 2668         | 5234XX.0409.9CT.FI |
| 400      | 24.4  | TB, TS, TW | 4000K       | CS, DA, NF   | 4031       | 2822         | 5234XX.0409.9CT.FI |
| 550      | 27.6  | TB, TS, TW | 3000K       | CS, DA, NF   | 4388       | 3072         | 5230XX.0609.9CT.FI |
| 550      | 27.6  | TB, TS, TW | 4000K       | CS, DA, NF   | 4747       | 3323         | 5230XX.0609.9CT.FI |
| 550      | 41.8  | TB, TS, TW | 3000K       | CS, DA, NF   | 6556       | 4589         | 5234XX.0609.9CT.FI |
| 550      | 41.8  | TB, TS, TW | 4000K       | CS, DA, NF   | 7099       | 4969         | 5234XX.0609.9CT.FI |
| 850      | 54.9  | TB, TS, TW | 3000K       | CS, DA, NF   | 8781       | 6147         | 5230XX.0909.9CT.FI |
| 850      | 54.9  | TB, TS, TW | 4000K       | CS, DA, NF   | 9330       | 6531         | 5230XX.0909.9CT.FI |
| 850      | 83    | TB, TS, TW | 3000K       | CS, DA, NF   | 13120      | 9184         | 5234XX.0909.9CT.FI |
| 850      | 83    | TB, TS, TW | 4000K       | CS, DA, NF   | 13951      | 9766         | 5234XX.0909.9CT.FI |
| 1110     | 97.3  | TB, TS, TW | 3000K       | CS, DA, NF   | 15565      | 10895        | 5230XX.1109.9CT.FI |
| 1110     | 97.3  | TB, TS, TW | 4000K       | CS, DA, NF   | 16580      | 11606        | 5230XX.1109.9CT.FI |
| 1110     | 151.5 | TB, TS, TW | 3000K       | CS, DA, NF   | 23940      | 16758        | 5234XX.1109.9CT.FI |
| 1110     | 151.5 | TB, TS, TW | 4000K       | CS, DA, NF   | 25524      | 17867        | 5234XX.1109.9CT.FI |

SELECT YOUR PREFERRED  
OPTION

| CONTROL TYPE      | XX | COLOR TEMP. | CT | FINISHING       | FI |
|-------------------|----|-------------|----|-----------------|----|
| CASAMBI           | CS | 3000K       | 30 | Textured Black  | TB |
| DALI / Switch Dim | DA | 4000K       | 40 | Textured Silver | TS |
| ON/OFF            | NF |             |    | Textured White  | TW |


**HELIUS SUSPENDED CRI→90**  
**PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - PRISMATIC**

| DIAMETER | POWER | FINISHING  | COLOR TEMP. | CONTROL TYPE | LED LUMENS | LUMINAIRE LM | CODE               |
|----------|-------|------------|-------------|--------------|------------|--------------|--------------------|
| 400      | 17.3  | TB, TS, TW | 3000K       | CS, DA, NF   | 2751       | 2201         | 5230XX.04P8.9CT.FI |
| 400      | 17.3  | TB, TS, TW | 4000K       | CS, DA, NF   | 2906       | 2325         | 5230XX.04P8.9CT.FI |
| 400      | 24.4  | TB, TS, TW | 3000K       | CS, DA, NF   | 3811       | 3049         | 5234XX.04P8.9CT.FI |
| 400      | 24.4  | TB, TS, TW | 4000K       | CS, DA, NF   | 4031       | 3225         | 5234XX.04P8.9CT.FI |
| 550      | 27.6  | TB, TS, TW | 3000K       | CS, DA, NF   | 4388       | 3511         | 5230XX.06P8.9CT.FI |
| 550      | 27.6  | TB, TS, TW | 4000K       | CS, DA, NF   | 4747       | 3798         | 5230XX.06P8.9CT.FI |
| 550      | 41.8  | TB, TS, TW | 3000K       | CS, DA, NF   | 6556       | 5245         | 5234XX.06P8.9CT.FI |
| 550      | 41.8  | TB, TS, TW | 4000K       | CS, DA, NF   | 7099       | 5679         | 5234XX.06P8.9CT.FI |
| 850      | 54.9  | TB, TS, TW | 3000K       | CS, DA, NF   | 8781       | 7025         | 5230XX.09P8.9CT.FI |
| 850      | 54.9  | TB, TS, TW | 4000K       | CS, DA, NF   | 9330       | 7464         | 5230XX.09P8.9CT.FI |
| 850      | 83    | TB, TS, TW | 3000K       | CS, DA, NF   | 13120      | 10496        | 5234XX.09P8.9CT.FI |
| 850      | 83    | TB, TS, TW | 4000K       | CS, DA, NF   | 13951      | 11161        | 5234XX.09P8.9CT.FI |
| 1110     | 97.3  | TB, TS, TW | 3000K       | CS, DA, NF   | 15565      | 12452        | 5230XX.11P8.9CT.FI |
| 1110     | 97.3  | TB, TS, TW | 4000K       | CS, DA, NF   | 16580      | 13264        | 5230XX.11P8.9CT.FI |
| 1110     | 151.5 | TB, TS, TW | 3000K       | CS, DA, NF   | 23940      | 19152        | 5234XX.11P8.9CT.FI |
| 1110     | 151.5 | TB, TS, TW | 4000K       | CS, DA, NF   | 25524      | 20419        | 5234XX.11P8.9CT.FI |

**SELECT YOUR PREFERRED OPTION**

| CONTROL TYPE             | XX | COLOR TEMP. | CT | FINISHING       | FI |
|--------------------------|----|-------------|----|-----------------|----|
| CASAMBI                  | CS | 3000K       | 30 | Textured Black  | TB |
| DALI / Switch Dim ON/OFF | DA | 4000K       | 40 | Textured Silver | TS |
|                          | NF |             |    | Textured White  | TW |

**ACCESSORIES**

|  |  |  |           |
|--|--|--|-----------|
|  | Suspension Kit<br>Suspension kit 1,5m (1un)<br>Suspension kit 3 m (1un)<br>Suspension kit 5 m (1un)                              | Silver<br>80303017.SL<br>80303018.SL<br>80303019.SL                            |           |
|  | Power Cable 0,75<br>Power Cable 1.5m<br>Power Cable 1.5m<br>Power Cable 3m<br>Power Cable 3m<br>Power Cable 5m<br>Power Cable 5m | ON/Off<br>80303001<br>80303004<br>80303002<br>80303005<br>80303003<br>80303006 | DALI Push |
|  | Recessed power box 200mm<br>Textured Black<br>Textured Silver<br>Textured white  | 120mm<br>50041023.TB<br>50041023.TS<br>50041023.TW                             |           |
|  | Ceiling Rose Surf. 120mm<br>Textured Black<br>Textured Silver<br>Textured white  | 120mm<br>50041024.TB<br>50041024.TS<br>50041024.TW                             |           |
|  | Surface ceiling box 120mm<br>120mm surface box TB<br>120mm surface box TS<br>120mm surface box TW                                | 120mm<br>50041025.TB<br>50041025.TS<br>50041025.TW                             |           |
|  | Surface ceiling box 200mm<br>200mm surface box TB<br>200mm surface box TS<br>200mm surface box TW                                | 200mm<br>50041027.TB<br>50041027.TS<br>50041027.TW                             |           |