

DESCRIPTION

NOTE: The price listed below is for 1 meter.
The item is sold in 5 meters reel, so the minimum order is 5 meters.
Please insert 5 units into the shopping cart, or multiples of this value.


Brilumen's Professional LED Strip is the brand's star and it stands out for its reliability, versatility and light quality, being considered the best LED strip on the market. With different wattages, luminous fluxes and widths, this 24V LED strip is available in the colour temperature from 2500K to 6500K, can have 30, 60, 120, 160 and 280 LED and a CRI higher than 80. The new Professional Strip with 280 LED/m stands out from the others strips for having 20W per meter and a large amount of LED, technical features that allows to build perfect light lines and with a higher luminous flux, up to 1900 lumens per meter. The 280 LED strip is available in the colour temperatures 2500K to 5000K and is extremely versatile, because it allows to cut the strip every 3 centimetres, without reducing the product's benefits. You can get an LED Strip with a 90 CRI and a R9→60. Due to the double-sided adhesive tape on the back, this product, besides being quite flexible, is easy to install and, depending on the model, is available with IP20 or IP67. To extend its operating cycle, it is recommended to install this LED strip in the right aluminium profile. When used properly, this high-quality LED strip for professional use, can be turned on 24 hours a day for 3 years without losing its features, and is highly recommended in numerous projects such as hotels, restaurants, shops, residences, etc. If the goal is to install a reliable, quality and easy to install product, Brilumen's Professional LED strip is undoubtedly the perfect choice.

MOUNTING TYPE	Surface
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	24V / 50-60 Hz
WARRANTY	5 Years
CONTROL	SMD2110


LED FEATURES

LUMINOUS EFFICIENCY	UP TO 95 lm/W
CRI	CRI→90

ICONOGRAPHY



TECHNICAL DRAWING



2002-153 20W/M 24H IP20
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - PROFESSIONAL 24H SMD2110 20W 280 LED IP20

POWER	VOLTAGE	COLOR TEMP.	RATED LUMINOUS FLUX/M	LED EFFICIENCY	UN.	CODE
20	24V	2500K	1539	77	5MT	2002-153.90.25
20	24V	2700K	1664	83	5MT	2002-153.90.27
20	24V	3000K	1767	88	5MT	2002-153.90.30
20	24V	4200K	1850	92	5MT	2002-153.90.42
20	24V	5000K	1903	95	5MT	2002-153.90.50

ACCESSORIES



Trix aluminium profile	8010-2002.AL
------------------------	--------------



IP20 LED Strip Connector	8013-0014
--------------------------	-----------



Connector w/ binder 15cm	8013-0015
--------------------------	-----------



Double c/t w/ binder	8013-0016
----------------------	-----------



L connector	8013-0017
-------------	-----------



12,5 mm Connector	8013-0026
-------------------	-----------



OP23 Corner Profile	SEM TITULO - G810-4052
---------------------	---------------------------



LP05 aluminium profile	SEM TITULO - G810-5201
------------------------	---------------------------




LP03 Recessed Profile	SEM TITULO - G810-6032
-----------------------	---------------------------



LP08 Recessed Profile	SEM TITULO - G810-6082
-----------------------	---------------------------



LP10 aluminium profile	SEM TITULO - G810-7012
------------------------	---------------------------



NP04 aluminium profile	SEM TITULO - G820-1012
------------------------	---------------------------



NP06 aluminium profile	SEM TITULO - G830-1017
------------------------	---------------------------



NP07 Recessed Profile	SEM TITULO - G830-5015
-----------------------	---------------------------



NP17 aluminium profile	SEM TITULO - G810-2026
------------------------	---------------------------



FP02 Edging Tile Profile	SEM TITULO - G810-2034
--------------------------	---------------------------



OP15 aluminium profile	SEM TITULO - G810-2062
------------------------	---------------------------



LP06 aluminium profile	SEM TITULO -
LP06 aluminium profile	G810-6062