

DESCRIPTION

INDYLINER, a new luminaire specific for indirect lighting, fully integrated in the top part of the 48V EVO track, TK9 model. The TK9 track allows for direct and/or indirect lighting, combining linear luminaires with track lights.

We highlight a new option for placing track lights on the top part of the track, using an articulated support, which allows the APALIS and/or ROSS track lights to be directed downwards, providing precise and effective lighting.

Our products guarantee exceptional light quality, with a high color rendering index, and a 5-year warranty, showing our confidence in their durability and reliability.

LIGHT DISTRIBUTION Direct POWER SUPPLY 48V / TRACK WARRANTY 5 Years

FINISHING Textured Black, Textured White CASAMBI, DALI, ON/OFF CONTROL

LED FEATURES

LUMINOUS EFFICIENCY UP TO 167 lm/W CRI→90 CRI LIFESPAN 50.000 Hours STEPS MACADAM 3 Steps MacAdam LUMEN MAINTENANCE L90/B50 PHOTOBIOLOGICAL RISK RG1

ICONOGRAPHY







INDYLINER OPAL 48V EVO PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - $CRI \rightarrow 90$

LENGTH				BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	
600	6.8	TB, TW	CS, DL, NF	90	1068	747	3000K	5226XX.0609.930.FI
600	6.8	TB, TW	CS, DL, NF	90	1136	795	4000K	5226XX.0609.940.FI
900	10.2	TB, TW	CS, DL, NF	90	1601	1121	3000K	5226XX.0909.930.FI
900	10.2	TB, TW	CS, DL, NF	90	1703	1192	4000K	5226XX.0909.940.FI

SELECT YOUR PREFERRED	CONTROL TYPE	XX	FINISHING	FI	BEAM ANGLE	ВА
OPTION	CASAMBI	CS	Textured Black	TB	90°	90
	DALI	DL	Textured White	TW		
	ON/OFF	NF				

ACCESSORIES





TECHNICAL DRAWING

