

DESCRIPTION

IRIS tubular 360° is an elegant lighting fixture with a minimalist design. It is available from 300mm to 1500mm lengths ranging. Drawing a perfect linear light, IRIS is suitable for lighting up effectively any indoor area through a beautiful, uniform and harmonious light. Tubular fixture composed of an opal polycarbonate tube and aluminium end caps; white or black textured finish; 360° light emission. IRIS can be suspended horizontally or vertically, surface mounted or recessed in the ceiling. It can also be placed in a magnetic or in a 3-circuits universal track. In both cases, it can be combined with other Brilumen track lights.

LIGHT DISTRIBUTION Direct
WARRANTY 5 Years
CONTROL N/A

LED FEATURES

CRI CRI→90
LIFESPAN 50.000 Hours
STEPS MACADAM 3 Steps MacAdam
LUMEN MAINTENANCE L90/B50
PHOTOBIOLOGICAL RISK RG1

ICONOGRAPHY

TECHNICAL DRAWING

IRIS TRACK HORIZ. 360
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROL TYPE	LED LUMENS	LUMINAIRE LM	CODE
626	17	TB, TW	3000K	N/A	2737	2258	5163H.06.930.FI
626	17	TB, TW	4000K	N/A	2907	2398	5163H.06.940.FI
926	23.8	TB, TW	3000K	N/A	3832	3161	5163H.09.930.FI
926	23.8	TB, TW	4000K	N/A	4070	3358	5163H.09.940.FI
1226	30.6	TB, TW	3000K	N/A	4927	4064	5163H.12.930.FI
1226	30.6	TB, TW	4000K	N/A	5233	4317	5163H.12.940.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	COLOR TEMP.	CT	FINISHING	FI
N/A	N/A	3000K	30	Textured Black	TB
		4000K	40	Textured White	TW

ACCESSORIES

230V Track ON/OFF White Black
230V Track ON/OFF 1M 3080-0300.WH 3080-0300.BL
230V Track ON/OFF 2M 3080-0301.WH 3080-0301.BL

230V Track DALI White Black
230V Track DALI 1M 3080-0517.WH 3080-0517.BL
230V Track DALI 2M 3080-0518.WH 3080-0518.BL

Recess. 230V Track ON/OFF White Black
230V Track ON/OFF 1M 3080-0336.WH 3080-0336.BL
230V Track ON/OFF 2M 3080-0337.WH 3080-0337.BL

Recessed 230V Track DALI
230V Track DALI 1M
230V Track DALI 2M

White	Black
3080-0553.WH	3080-0553.BL
3080-0554.WH	3080-0554.BL

230V Track C. Kit
Textured Black

ON/Off	DALI Push	CASAMBI
278NF.06.TB,	278DA.06.TB,	278CS.06.TB,
278NF.09.TB,	278DA.09.TB,	278CS.09.TB,
278NF.12.TB	278DA.12.TB	278CS.12.TB
278NF.06.TW,	278DA.06.TW,	278CS.06.TW,
278NF.09.TW,	278DA.09.TW,	278CS.09.TW,
278NF.12.TW	278DA.12.TW	278CS.12.TW

Textured White

230V Track C. Kit 926MM
230V Track C. Kit 926MM

SEM TITULO -
27809AV

230V Track C. Kit 1226MM
230V Track C. Kit 1226MM

SEM TITULO -
27812AV