

DESCRIPTION

IRIS tubular 360° is an elegant lighting fixture with a minimalist design. It is available from 300mm to 1500mm lengths ranging. Drawing a perfect linear light, IRIS is suitable for lighting up effectively any indoor area through a beautiful, uniform and harmonious light. Tubular fixture composed of an opal polycarbonate tube and aluminium end caps; white or black textured finish; 360° light emission. IRIS can be suspended horizontally or vertically, surface mounted or recessed in the ceiling. It can also be placed in a magnetic or in a 3-circuits universal track. In both cases, it can be combined with other Brilumen track lights.


| | |
|--------------------|--------------------------------|
| LIGHT DISTRIBUTION | Direct |
| WARRANTY | 5 Years |
| FINISHING | Textured Black, Textured White |
| CONTROL | N/A |



LED FEATURES

| | |
|----------------------|-----------------|
| LUMINOUS EFFICIENCY | UP TO 167 lm/W |
| CRI | CRI→90 |
| LIFESPAN | 50.000 Hours |
| STEPS MACADAM | 3 Steps MacAdam |
| LUMEN MAINTENANCE | L90/B50 |
| PHOTOBIOLOGICAL RISK | RG1 |

ICONOGRAPHY



IRIS VERTICAL 360 1240MM
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90

| LENGTH | POWER | FINISHING | COLOR TEMP. | CONTROLTYPE | LED LUMENS | LUMINAIRE LM | CODE |
|--------|----------|-----------|-------------|-------------|------------|--------------|----------------|
| 1240 | 28,10835 | TB, TW | 3000K | N/A | 4408 | 3637 | 163V.12.930.FI |
| 1240 | 28,10835 | TB, TW | 4000K | N/A | 4667 | 3850 | 163V.12.940.FI |

SELECT YOUR PREFERRED
OPTION

| CONTROLTYPE | XX | COLOR TEMP. | CT | FINISHING | FI |
|-------------|-----|-------------|----|----------------|----|
| N/A | N/A | 3000K | 30 | Textured Black | TB |
| | | 4000K | 40 | Textured White | TW |

ACCESSORIES

SEM DescAbr - SEM TITULO -
SEM DescAbr - 270AV 270AV

SEM DescAbr - SEM TITULO -
SEM DescAbr - 271AV 271AV

SEM DescAbr - SEM TITULO -
SEM DescAbr - 272AV 272AV