

DESCRIPTION

IRIS tubular 360° is an elegant lighting fixture with a minimalist design. It is available from 340mm to 640mm lengths ranging. Drawing a perfect linear light, IRIS is suitable for lighting up effectively any indoor area through a beautiful, uniform and harmonious light. Tubular fixture composed of an opal polycarbonate tube and aluminium end caps; white or black textured finishin; 360° light emission. IRIS can be suspended horizontally or vertically, surface mounted or recessed in the ceiling. It can also be placed in a magnetic or in a 3-circuits universal track. In both cases, it can be combined with other Brilumen track lights.

LIGHT DISTRIBUTION	Direct
WARRANTY	5 Years
FINISHING	Textured Black, Textured White
CONTROL	N/A

LED FEATURES

LUMINOUS EFFICIENCY	UP TO 167 lm/W
CRI	CRI→90
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY



IRIS 48V TRACK VERT. 360
 PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROL TYPE	LED LUMENS	LUMINAIRE LM	CODE
340	7.8	TB, TW	3000K	N/A	1225	1011	163V.03.930.FI
340	7.8	TB, TW	4000K	N/A	1297	1070	163V.03.940.FI
640	15.6	TB, TW	3000K	N/A	2449	2021	163V.06.930.FI
640	15.6	TB, TW	4000K	N/A	2593	2140	163V.06.940.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX
N/A	N/A

COLOR TEMP.	CT
3000K	30
4000K	40

FINISHING	FI
Textured Black	TB
Textured White	TW



TECHNICAL DRAWING



ACCESSORIES



IRIS 48V Track Vert. Kit	ON/Off	DALI	CASAMBI
340mm Textured Black	274NF.03.TB	274DL.03.TB	274CS.03.TB
340mm Textured White	274NF.03.TW	274DL.03.TW	274CS.03.TW
640mm Textured Black	274NF.06.TB	274DL.06.TB	274CS.06.TB
640mm Textured White	274NF.06.TW	274DL.06.TW	274CS.06.TW



BT1 Magnetic Track	White	Black
Magnetic Track 48V 1M	3080-0175.WH	3080-0175.BL
Magnetic Track 48V 2M	3080-0176.WH	3080-0176.BL



BT2 Magnetic Track	White	Black
Magnetic Track 48V 1M	3080-0177.WH	3080-0177.BL
Magnetic Track 48V 2M	3080-0178.WH	3080-0178.BL



TK3 Magnetic Track	White	Black
Magnetic Track 48V 1M	3080-0205.WH	3080-0205.BL
Magnetic Track 48V 2M	3080-0206.WH	3080-0206.BL




TK5 48V Magnetic Track	White	Black
Magnetic Track 48V 1M	3080-0250.WH	3080-0250.BL
Magnetic Track 48V 2M	3080-0251.WH	3080-0251.BL


TK9 Magnetic Track	White	Black
--------------------	-------	-------




Magnetic Track 48V 1M	3080-0211.WH	3080-0211.BL
Magnetic Track 48V 2M	3080-0212.WH	3080-0212.BL



Power Cable 1.5m	ON/Off
Power Cable 1.5m	80303001



Clear Power Cable 3m	ON/Off
Clear Power Cable 3m	80303002



Power Cable 5m	ON/Off
Power Cable 5m	80303003