

DESCRIPTION

IRIS vertical connection kit - Oval surface

MOUNTING	Surface
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Textured Black, Textured White
CONTROL	CASAMBI, DALI / PUSH Dim, ON/OFF



ICONOGRAPHY



ACCESSORIES

Conn. Kit - OVAL SURFACE	CASAMBI	DALI Push	ON/OFF
340 mm Textured Black	271CS.03.TB		
340 mm Textured White	271CS.03.TW		
640 mm Textured Black	271CS.06.TB		
640 mm Textured White	271CS.06.TW		
940 mm Textured Black	271CS.09.TB		
940 mm Textured White	271CS.09.TW		
1240 mm Textured Black	271CS.12.TB		
1240 mm Textured White	271CS.12.TW		
1540 mm Textured Black	271CS.15.TB		
1540 mm Textured White	271CS.15.TW		
340 mm Textured Black		271DA.03.TB	
340 mm Textured White		271DA.03.TW	
640 mm Textured Black		271DA.06.TB	
640 mm Textured White		271DA.06.TW	
940 mm Textured Black		271DA.09.TB	
940 mm Textured White		271DA.09.TW	
1240 mm Textured Black		271DA.12.TB	
1240 mm Textured White		271DA.12.TW	
1540 mm Textured Black		271DA.15.TB	
1540 mm Textured White		271DA.15.TW	
340 mm Textured Black			271NF.03.TB
340 mm Textured White			271NF.03.TW
640 mm Textured Black			271NF.06.TB
640 mm Textured White			271NF.06.TW
940 mm Textured Black			271NF.09.TB
940 mm Textured White			271NF.09.TW
1240 mm Textured Black			271NF.12.TB
1240 mm Textured White			271NF.12.TW
1540 mm Textured Black			271NF.15.TB
1540 mm Textured White			271NF.15.TW