


DESCRIPTION

IRIS V 360°, with an IP65, marks a new twist in the IRIS 360° lighting range, which until now was only available with an IP40. This elegant new luminaire, with a minimalist design, extends the use of the 360° range as it can be applied whenever a waterproof, IP65 fixture is required. Tubular fixture composed of an opal polycarbonate tube and aluminium end caps. It is possible to install it outdoors as long as it is protected from direct sunlight.

MOUNTING TYPE	Suspension
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Anodized aluminium
CONTROL	DALI, ON/OFF


LED FEATURES

LUMINOUS EFFICIENCY	UP TO 171 lm/W
CRI	CRI→90
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY





**IRIS WATERPROOF 360° IP65
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90**

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROL TYPE	LED LUMENS	LUMINAIRE LM	CODE
660	17	AL	3000K	DL, NF	2737	2258	5207XX.06.930.FI
660	17	AL	4000K	DL, NF	2907	2398	5207XX.06.940.FI
960	23.8	AL	3000K	DL, NF	3832	3161	5207XX.09.930.FI
960	23.8	AL	4000K	DL, NF	4070	3358	5207XX.09.940.FI
1260	30.6	AL	3000K	DL, NF	4927	4064	5207XX.12.930.FI
1260	30.6	AL	4000K	DL, NF	5233	4317	5207XX.12.940.FI
1560	40.8	AL	3000K	DL, NF	6569	5419	5207XX.15.930.FI
1560	40.8	AL	4000K	DL, NF	6977	5756	5207XX.15.940.FI

**SELECT YOUR PREFERRED
OPTION**

CONTROL TYPE	XX	COLOR TEMP.	CT	FINISHING	FI
DALI	DL	3000K	30	Anodized aluminium	AL
ON/OFF	NF	4000K	40		

ACCESSORIES

	Power Cable 1.5m Power Cable 1.5m	ON/Off 80303001
	Power Cable 3m Power Cable 3m	ON/Off 80303002
	Power Cable 5m Power Cable 5m	ON/Off 80303003