# . brilumen

## DESCRIPTION

LAZULI is a thin and elegant pendant light with a high-quality textured black or white finish that creates unique environments. It is available in four versions, one for recessed ceiling, one for surface, one for application in

magnetic track and another for 3 circuit 230V universal track.

MOUNTING TYPE LIGHT DISTRIBUTION POWER SUPPLY WARRANTY FINISHING CONTROL

Uni Track Direct 220-230V / 50-60 Hz 5 Years Textured Black, Textured White CASAMBI, DALI / Switch Dim, ON/OFF

### LED FEATURES

ICONOGRAPHY

5

LUMINOUS EFFICIENCY CRI LIFESPAN STEPS MACADAM LUMEN MAINTENANCE PHOTOBIOLOGICAL RISK

()

UP TO 129 lm/W CRI→90 50.000 Hours 3 Steps MacAdam L90/B50 RG1

# TECHNICAL DRAWING

CRI >90

### LAZULI UNIVERSAL 230V

PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI $\rightarrow$ 90

			ONTROL TYPE BEA	MANGLE LEI	DLUMENS LUM	NAIRE LM COL	LOR TEMP.	
400	6.5	TB, TW	CS, DA, NF	35	822	699	3000K	498XX.35.930.FI
400	6.5	TB, TW	CS, DA, NF	35	835	710	4000K	498XX.35.940.FI

1

SELECT YOUR PREFERRED	CONTROL TYPE	XX	FINISHING	FI
OPTION	CASAMBI	CS	Textured Black	TB
	DALI / Switch Dim	DA	Textured White	TW
	ON/OFF	NF		

### ACCESSORIES

	Track ON/OFF Susp./Surf.		
	ON/OFF Track 1m Black	UP1459302-1	
	0N/0FF Track 1m White	UP1459102-1	
	ON/OFF Track 2m Black	UP1459302	
	ON/OFF Track 2m White	UP1459102	
	Track DALI Susp./Surf.		
	DALI Track 1m Black	UP1459307-1	
	DALI Track 1m White	UP1459107-1	
	DALI Track 2m Black	UP1459307	
	DALI Track 2m White	UP1459107	
	Recess. Track ON/OFF		
	ON/OFF Rec. Track 1m BL	UP1459312-1	
	0N/0FF Rec. Track 1m WH	UP1459112-1	
	0N/0FF Rec. Track 2m BL	UP1459312	
	0N/0FF Rec. Track 2m WH	UP1459112	
	Recessed Track DALI		
	DALI Rec. Track 1m BL	UP1459317-1	
	DALI Rec. Track 1m WH	UP1459117-1	
	DALI Rec. Track 2m BL	UP1459317	
	DALI Rec. Track 2m WH	UP1459117	
	Lazuli Power Cable	Textured White	Textured Black
ð	Power Cable 1,5M	30800241.TW	30800241.TB
0	Power Cable 1M	30800240.TW	30800240.TB
	Power Cable 2M	30800242.TW	30800242.TB