

DESCRIPTION


LAZULI DOUBLE is a thin and elegant pendant light with a high-quality textured black or white finish that creates unique environments. LAZULI DOUBLE brings together 2 LAZULI in the same driver, allowing on the one hand to reduce the space between the track lights thus changing the aesthetics, and on the other hand to reduce the total cost of the solution. Due to the specificity of the driver, this product is only available for regulation through the DALI protocol, with magnetic tracks.

MOUNTING TYPE	Magnetic
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	48V / TRACK
WARRANTY	5 Years
FINISHING	Textured Black, Textured White
CONTROL	DALI

LED FEATURES

LUMINOUS EFFICIENCY	UP TO 130 lm/W
CRI	CRI→90
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY



LAZULI DOUBLE MAGNETIC
 PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90

LENGTH	POWER	FINISHING	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
400	11	TB, TW	DL	35	1392	1184	3000K	480XX.35.930.FI
400	11	TB, TW	DL	35	1414	1202	4000K	480XX.35.940.FI


SELECT YOUR PREFERRED
 OPTION

CONTROL TYPE	XX
DALI	DL

FINISHING	FI
Textured Black	TB
Textured White	TW



TECHNICAL DRAWING



ACCESSORIES



BT1 Magnetic Track	White	Black
Magnetic Track 48V 1M	3080-0175.WH	3080-0175.BL
Magnetic Track 48V 2M	3080-0176.WH	3080-0176.BL



BT2 Magnetic Track	White	Black
Magnetic Track 48V 1M	3080-0177.WH	3080-0177.BL
Magnetic Track 48V 2M	3080-0178.WH	3080-0178.BL



Lazuli Power Cable	Textured White	Textured Black
Power Cable 1,5M	30800241.TW	30800241.TB
Power Cable 1M	30800240.TW	30800240.TB
Power Cable 2M	30800242.TW	30800242.TB



TK3 Magnetic Track	White	Black
Magnetic Track 48V 1M	3080-0205.WH	3080-0205.BL
Magnetic Track 48V 2M	3080-0206.WH	3080-0206.BL



TK5 48V Magnetic Track	White	Black
Magnetic Track 48V 1M	3080-0250.WH	3080-0250.BL
Magnetic Track 48V 2M	3080-0251.WH	3080-0251.BL



TK9 Magnetic Track	White	Black
Magnetic Track 48V 1M	3080-0211.WH	3080-0211.BL
Magnetic Track 48V 2M	3080-0212.WH	3080-0212.BL