

DESCRIPTION

LAZULI is a thin and elegant pendant light with a high-quality textured black or white finish that creates unique environments.


It is available in four versions, one for recessed ceiling, one for surface, one for application in 48V EVO track and another for 3-circuit 230V universal track.

LAZULI DOUBLE brings together 2 LAZULI in the same driver, allowing on one hand to reduce the space between the track lights thus changing the aesthetics, and on the other hand to reduce the total cost of the solution.

MOUNTING	Suspension
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Textured Black, Textured White
CONTROL	DALI / PUSH Dim, ON/OFF




TECHNICAL DRAWING



LED FEATURES

LUMINOUS EFFICIENCY	UP TO 133 lm/W
CRI	CRI→90
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY



LAZULI RECESSED SPOTLIGHT
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90

LENGTH	POWER	FINISHING	CONTROLTYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
400	6,3	TB, TW	DA, NF	35	756	643	2700K	5406XX.35.927.FI
400	6,3	TB, TW	DA, NF	35	788	669	3000K	5406XX.35.930.FI
400	6,3	TB, TW	DA, NF	35	838	712	4000K	5406XX.35.940.FI

SELECT YOUR PREFERRED OPTION

CONTROLTYPE	XX	FINISHING	FI
DALI / PUSH Dim	DA	Textured Black	TB
ON/OFF	NF	Textured White	TW

ACCESSORIES

	Power Cable 1M	Textured White	Textured Black
	Power Cable 1M	30800240.TW	30800240.TB

	Power Cable 1,5M	Textured White	Textured Black
	Power Cable 1,5M	30800241.TW	30800241.TB