

## DESCRIPTION

Brilumen features a collection of versatile, modern and stylish wall light fittings and which, depending on the design, beam angle and lumens, are suitable for different types of outdoor areas. If the goal is to light both up and down, Marley, Miller and Tosh are the best option, not forgetting that this last wall light has an optional reflector that allows you to close the beam angle. If you want to get a linear light line, the Wailer 16W is the right light fitting. However, if you are looking for a wall lighting to light a pathway, the recessed Levy 4W completes the goal efficiently. These products have an IP54 and are available in dark grey finish.


MOUNTING TYPE	Surface
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	2 Years
FINISHING	TG
CONTROL	ON/OFF




## LED FEATURES

LUMINOUS EFFICIENCY	UP TO 47 lm/W
CRI	CRI→80
LIFESPAN	30000h Tp55
STEPS MACADAM	5 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

## TECHNICAL DRAWING



## ICONOGRAPHY



## LEVY 4W PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80

LENGTH	POWER	FINISHING	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
66	4	TG	NF	20	180	160	3000K	509.80.BA.30
66	4	TG	NF	20	189	168	4000K	509.80.BA.40

SELECT YOUR PREFERRED  
OPTION

CONTROL TYPE	XX
ON/OFF	NF

PHOTOMETRIC DATA

POLAR DIAGRAM AND LUMINOUS FLUX - LENS Titulo

