. brilumen

DESCRIPTION

Brilumen features a collection of versatile, modern and stylish wall light fittings and which, depending on the design, beam angle and lumens, are suitable for different types of outdoor areas. If the goal is to light both up and down, Marley, Miller and Tosh are the best option, not forgetting that this last wall light has an optional reflector that allows you to close the beam angle. If you want to get a linear light line, the Wailer 16W is the right light fitting. However, if you are looking for a wall lighting to light a pathway, the recessed Levy 4W completes the goal efficiently. These products have an IP54 and are available in dark grey finish.

MOUNTING TYPE LIGHT DISTRIBUTION POWER SUPPLY WARRANTY FINISHING CONTROL

LED FEATURES

Surface Direct 220-230V / 50-60 Hz 2 Years TG 0N/0FF

UP TO 47 lm/W


5 Steps MacAdam L90/B50

30000h Tp55

CRI→80

RG1

TECHNICAL DRAWING



LUMINOUS EFFICIENCY CRI LIFESPAN STEPS MACADAM LUMEN MAINTENANCE PHOTOBIOLOGICAL RISK

ICONOGRAPHY



	LEVY 4W PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI->80								
				BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.		
66	4	TG	NF	20	180	160	3000K	509.80.BA.30	
66	4	TG	NF	20	189	168	4000K	509.80.BA.40	

1

SELECT YOUR PREFERRED	CONTROL TYPE	XX
OPTION	ON/OFF	NF

. brilumen

PHOTOMETRIC DATA

POLAR DIAGRAM AND LUMINOUS FLUX - LENS Titulo

