

DESCRIPTION

A lighting solution created to unite performance, precision, and personality. LLOYD redefines technical lighting with an impactful design, where every detail reflects Brilumen's commitment to excellence and aesthetic clarity. Available in multiple installation options surface-mounted or suspended ceiling (indirect light option available), and adaptable to low-voltage 48V EVO tracks as well as universal 3-circuit tracks (230V) LLOYD is engineered to meet the specific requirements of any architectural layout. Defined by silent confidence, LLOYD doesn't just light it defines. For application as a track light, the adjustable version, with a sculptural squared form and a clustered lens composition, adds character to any space while delivering precise, directional lighting.

| | |
|--------------------|--------------------------------|
| MOUNTING TYPE | CALHAS |
| LIGHT DISTRIBUTION | Direct |
| POWER SUPPLY | 48V / TRACK |
| WARRANTY | 5 Years |
| FINISHING | Textured Black, Textured White |
| CONTROL | CASAMBI, DALI, ON/OFF |



LED FEATURES

| | |
|----------------------|-----------------|
| LUMINOUS EFFICIENCY | UP TO 174 lm/W |
| CRI | CRI→90 |
| LIFESPAN | 50.000 Hours |
| STEPS MACADAM | 3 Steps MacAdam |
| LUMEN MAINTENANCE | L90/F10 |
| PHOTOBIOLOGICAL RISK | RG1 |

TECHNICAL DRAWING

ICONOGRAPHY



LLOYD 48V EVO
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90

| LENGTH | POWER | FINISHING | CONTROL TYPE | BEAM ANGLE | LED LUMENS | LUMINAIRE LM | COLOR TEMP. | CODE |
|--------|-------|-----------|--------------|----------------|------------|--------------|-------------|-----------------|
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2464 | 2340 | 3000K | 573XX.14.930.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2464 | 2340 | 3000K | 573XX.25.930.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2464 | 2340 | 3000K | 573XX.36.930.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2464 | 2340 | 3000K | 573XX.75.930.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2464 | 2340 | 3000K | 582XX.14.930.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2464 | 2340 | 3000K | 582XX.25.930.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2464 | 2340 | 3000K | 582XX.36.930.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2464 | 2340 | 3000K | 582XX.75.930.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2614 | 2483 | 4000K | 573XX.14.940.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2614 | 2483 | 4000K | 573XX.25.940.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2614 | 2483 | 4000K | 573XX.36.940.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2614 | 2483 | 4000K | 573XX.75.940.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2614 | 2483 | 4000K | 582XX.14.940.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2614 | 2483 | 4000K | 582XX.25.940.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2614 | 2483 | 4000K | 582XX.36.940.FI |
| 290 | 15 | TB, TW | CS, DL, NF | 14, 25, 36, 75 | 2614 | 2483 | 4000K | 582XX.75.940.FI |

SELECT YOUR PREFERRED
OPTION

| CONTROL TYPE | XX | FINISHING | FI | BEAM ANGLE | BA |
|--------------|----|----------------|----|------------|----|
| CASAMBI | CS | Textured Black | TB | 14° | 14 |
| DALI | DL | Textured White | TW | 25° | 25 |
| ON/OFF | NF | | | 36° | 36 |
| | | | | 75° | 75 |