


DESCRIPTION

Brilumen is specialize in technical lighting, suitable for stores, supermarkets, shopping centres, art galleries, museums, restaurants, etc. In these places, lighting the product or areas correctly is fundamental to highlight all the details and get the customers attention. The Brilumen track lights are the ideal solution for highlighting products in any location. With this light fitting range, you can get the right luminous flux, an excellent colour temperature and a low UGR, maintaining controlled, the visual comfort, room temperature and energy costs. In addition, these track lights have an 80 or 95 CRI and are adjustable, allowing not only to adjust them whenever the place is changed, making it more dynamic, but also to easily guide the customers. The Brilumen track lights have already been used in countless lighting projects, such as commercial areas, museums, car dealerships, exhibitors in trade shows, etc.

MOUNTING TYPE	Uni Track
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	2 Years
FINISHING	Textured Black, Textured White
CONTROL	ON/OFF


LED FEATURES

LUMINOUS EFFICIENCY	UP TO 88 lm/W
CRI	CRI→80, CRI→95
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY

LORY 12W
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80

LENGTH	POWER	FINISHING	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
60	12	TB, TW	NF	24, 38	1056	975	2700K	442.80.BA.27.FI
60	12	TB, TW	NF	24, 38	1056	975	3000K	442.80.BA.30.FI
60	12	TB, TW	NF	24, 38	1056	975	4000K	442.80.BA.40.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	FINISHING	FI	BEAM ANGLE	BA
ON/OFF	NF	Textured Black	TB	24°	24
		Textured White	TW	38°	38


LORY 12W
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→95

LENGTH	POWER	FINISHING	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
60	12	TB, TW	NF	24, 38	840	775	2700K	442.95.BA.27.FI
60	12	TB, TW	NF	24, 38	840	775	3000K	442.95.BA.30.FI
60	12	TB, TW	NF	24, 38	840	775	4000K	442.95.BA.40.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	FINISHING	FI	BEAM ANGLE	BA
ON/OFF	NF	Textured Black	TB	24°	24
		Textured White	TW	38°	38

ACCESSORIES


Track ON/OFF Susp./Surf.	
ON/OFF Track 1m White	UP1459102-1
ON/OFF Track 2m White	UP1459102
SEM DescAbr - UP1459429	UP1459429
SEM DescAbr - UP1459429-1	UP1459429-1
Track DALI Susp./Surf.	
DALI Track 1m White	UP1459107-1



DALI Track 2m White
SEM DescAbr - UP1459439
SEM DescAbr - UP1459439-1

UP1459107
UP1459439
UP1459439-1



Recess. Track ON/OFF
ON/OFF Rec. Track 1m BL
ON/OFF Rec. Track 1m WH
ON/OFF Rec. Track 2m BL
ON/OFF Rec. Track 2m WH

UP1459312-1
UP1459112-1
UP1459312
UP1459112



Recessed Track DALI
DALI Rec. Track 1m BL
DALI Rec. Track 1m WH
DALI Rec. Track 2m BL
DALI Rec. Track 2m WH

UP1459317-1
UP1459117-1
UP1459317
UP1459117