


DESCRIPTION

Considered the best LED panel on the market, the versatile Matrix EVO is a ready-to-install LED panel equipped with high-quality LEDs. It has a unified glare rating (UGR) of less than 19 and can be used in areas with very different sizes, such as waiting rooms, offices, supermarkets, shopping centres and airports.

Available in two sizes, 600x600mm and 1200x300mm, Matrix EVO can be recessed or suspended from the ceiling.


MOUNTING	SUSPENSÃO - SALIENTE - ENCASTRAR
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	White
CONTROL	CASAMBI, DALI / PUSH Dim, ON/OFF




LED FEATURES

LUMINOUS EFFICIENCY	UP TO 133 lm/W
CRI	CRI→80
LIFESPAN	50.000 Hours
STEPS MACADAM	4 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

TECHNICAL DRAWING



ICONOGRAPHY



MATRIX EVO 600X600MM
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80

LENGTH	POWER	FINISHING	CONTROLTYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
595	23,3	WH	CS, DA, NF	90	3430	2918	3000K	5298XX.06.830
595	23,3	WH	CS, DA, NF	90	3650	3104	4000K	5298XX.06.840
595	31,7	WH	CS, DA, NF	90	4510	3833	3000K	5299XX.06.830
595	31,7	WH	CS, DA, NF	90	4770	4055	4000K	5299XX.06.840

SELECT YOUR PREFERRED OPTION

CONTROLTYPE	XX	FINISHING	FI	BEAM ANGLE	BA
CASAMBI	CS	White	WH	90°	90
DALI / PUSH Dim	DA				
ON/OFF	NF				

ACCESSORIES

	Recessed frame 600x600	-	
	Recessed frame 600x600	3080-011	
	White surface frame 600	-	
	White surface frame 600	8030-2368	
	Y Suspens. kit Matrix EVO	-	
	Y Suspens. kit Matrix EVO	8030-2369	