




DESCRIPTION

A circle is the reflection of eternity, it has no beginning and it has no end. Brilumen proudly presents our new range of circular LED luminaires. With a 5 Year Warranty Olympia is designed and inspired to deliver one continuous and seamless line of light. With an internal driver, different wattages, diameters and mounting types, these circular profiles can be easily applied in numerous locations, such as stores, cinemas, museums, galleries, hotels, restaurants, meeting rooms, offices, lounges, etc. The Olympia LED circular profile can also be configured with the options of ON-OFF, DALI and CASAMBI. Other dimmable options are as well available on request. Brilumen has also available the IES and LDT files for DIALux projects, providing technical assistance during lighting projects.

MOUNTING	Surface
LIGHT DISTRIBUTION	Directa
POWER SUPPLY	220-230V / 50/60 Hz, 220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Textured Black, Textured Silver, Textured White
CONTROL	DALI / PUSH Dim, ON/OFF


LED FEATURES

LUMINOUS EFFICIENCY	UP TO 191 lm/W
CRI	CRI→80
LIFESPAN	40.000 Hours Tp 55°
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/F10
PHOTOBIOLOGICAL RISK	RG0

TECHNICAL DRAWING

ICONOGRAPHY

**OLYMPIA SURFACE
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - OPAL**

DIAMETER	POWER	FINISHING	COLOR TEMP.	CONTROLTYPE	LED LUMENS	LUMINAIRE LM	CODE
620	41	TB, TS, TW	3000K	DA, NF	7320	6149	181XX.0609.8CT.FI
620	41	TB, TS, TW	4000K	DA, NF	7800	6552	181XX.0609.8CT.FI
920	62	TB, TS, TW	3000K	DA, NF	10980	9125	181XX.0909.8CT.FI
920	62	TB, TS, TW	4000K	DA, NF	11700	9723	181XX.0909.8CT.FI
1220	82	TB, TS, TW	3000K	DA, NF	14640	12152	181XX.1209.8CT.FI
1220	82	TB, TS, TW	4000K	DA, NF	15600	12948	181XX.1209.8CT.FI
1520	109	TB, TS, TW	3000K	DA, NF	19520	16261	181XX.1509.8CT.FI
1520	109	TB, TS, TW	4000K	DA, NF	20800	17327	181XX.1509.8CT.FI

SELECT YOUR PREFERRED
OPTION

CONTROLTYPE	XX	COLOR TEMP.	CT	FINISHING	FI
DALI / PUSH Dim	DA	3000K	30	Textured Black	TB
ON/OFF	NF	4000K	40	Textured Silver	TS
				Textured White	TW


**OLYMPIA SURFACE
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - PRISMATIC**

DIAMETER	POWER	FINISHING	COLOR TEMP.	CONTROLTYPE	LED LUMENS	LUMINAIRE LM	CODE
620	41	TB, TS, TW	3000K	DA, NF	7320	6831	181XX.06P8.8CT.FI
620	41	TB, TS, TW	4000K	DA, NF	7800	7279	181XX.06P8.8CT.FI
920	62	TB, TS, TW	3000K	DA, NF	10980	10070	181XX.09P8.8CT.FI
920	62	TB, TS, TW	4000K	DA, NF	11700	10730	181XX.09P8.8CT.FI
1220	82	TB, TS, TW	3000K	DA, NF	14640	13452	181XX.12P8.8CT.FI
1220	82	TB, TS, TW	4000K	DA, NF	15600	14334	181XX.12P8.8CT.FI
1520	109	TB, TS, TW	3000K	DA, NF	19520	18155	181XX.15P8.8CT.FI
1520	109	TB, TS, TW	4000K	DA, NF	20800	19345	181XX.15P8.8CT.FI

SELECT YOUR PREFERRED
OPTION

CONTROLTYPE	XX	COLOR TEMP.	CT	FINISHING	FI
DALI / PUSH Dim	DA	3000K	30	Textured Black	TB
ON/OFF	NF	4000K	40	Textured Silver	TS
				Textured White	TW

ACCESSORIES




CASAMBI - DALI Interface
CASAMBI - DALI Interface

CASAMBI
8030-2590

PHOTOMETRIC DATA

POLAR DIAGRAM AND LUMINOUS FLUX - LENS OPAL



PHOTOMETRIC DATA

POLAR DIAGRAM AND LUMINOUS FLUX - LENS PRISMATIC

