

DESCRIPTION

A circle is the reflection of eternity; it has no beginning and no end. Backed by a 5-year warranty, the OLYMPIA and HELIUS luminaires were designed and inspired to provide high-quality ambient lighting. With a built-in driver available in various wattages, diameters, and mounting options, these circular profiles can be easily installed in a wide range of spaces, such as shops, museums, galleries, hotels, restaurants, offices, meeting rooms, or waiting areas, among others.

MOUNTING	Suspension
DISTRIBUICAO LUZ	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Textured Black, Textured Silver, Textured White
CONTROL	CASAMBI, DALI / Switch Dim, ON/OFF


LED FEATURES

LUMINOUS EFFICIENCY	UP TO 165 lm/W
CRI	CRI→90
LIFESPAN	72000h Tp55
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/F10
PHOTOBIOLOGICAL RISK	RG0

ICONOGRAPHY



TECHNICAL DRAWING



OLYMPIA SUSPENDED CRI→90
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - OPAL

DIAMETER	POWER	FINISHING	COLOR TEMP.	CONTROLTYPE	LED LUMENS	LUMINAIRE LM	CODE
620	39.6	TB, TS, TW	3000K	CS, DA, NF	6296	4407	5232XX.0609.9CT.FI
620	39.6	TB, TS, TW	4000K	CS, DA, NF	6534	4574	5232XX.0609.9CT.FI
920	59.4	TB, TS, TW	3000K	CS, DA, NF	9445	6611	5232XX.0909.9CT.FI
920	59.4	TB, TS, TW	4000K	CS, DA, NF	9801	6861	5232XX.0909.9CT.FI
1220	79.2	TB, TS, TW	3000K	CS, DA, NF	12593	8815	5232XX.1209.9CT.FI
1220	79.2	TB, TS, TW	4000K	CS, DA, NF	13068	9148	5232XX.1209.9CT.FI
1520	105.6	TB, TS, TW	3000K	CS, DA, NF	16790	11753	5232XX.1509.9CT.FI
1520	105.6	TB, TS, TW	4000K	CS, DA, NF	17424	12197	5232XX.1509.9CT.FI

SELECT YOUR PREFERRED
OPTION

CONTROLTYPE	XX	COLOR TEMP.	CT	FINISHING	FI
CASAMBI	CS	3000K	30	Textured Black	TB
DALI / Switch Dim	DA	4000K	40	Textured Silver	TS
ON/OFF	NF			Textured White	TW


OLYMPIA SUSPENDED CRI→90
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - PRISMATIC

DIAMETER	POWER	FINISHING	COLOR TEMP.	CONTROLTYPE	LED LUMENS	LUMINAIRE LM	CODE
620	39.6	TB, TS, TW	3000K	CS, DA, NF	6296	5037	5232XX.06P8.9CT.FI
620	39.6	TB, TS, TW	4000K	CS, DA, NF	6534	5227	5232XX.06P8.9CT.FI
920	59.4	TB, TS, TW	3000K	CS, DA, NF	9445	7556	5232XX.09P8.9CT.FI
920	59.4	TB, TS, TW	4000K	CS, DA, NF	9801	7841	5232XX.09P8.9CT.FI
1220	79.2	TB, TS, TW	3000K	CS, DA, NF	12593	10074	5232XX.12P8.9CT.FI
1220	79.2	TB, TS, TW	4000K	CS, DA, NF	13068	10454	5232XX.12P8.9CT.FI
1520	105.6	TB, TS, TW	3000K	CS, DA, NF	16790	13432	5232XX.15P8.9CT.FI
1520	105.6	TB, TS, TW	4000K	CS, DA, NF	17424	13939	5232XX.15P8.9CT.FI

SELECT YOUR PREFERRED OPTION

CONTROLTYPE	XX	COLOR TEMP.	CT	FINISHING	FI
CASAMBI	CS	3000K	30	Textured Black	TB
DALI / Switch Dim ON/OFF	DA	4000K	40	Textured Silver	TS
	NF			Textured White	TW

ACCESSORIES

	Suspension Kit	Silver	
	Suspension kit 1,5m (1un)	80303017.SL	
	Suspension kit 3 m (1un)	80303018.SL	
	Suspension kit 5 m (1un)	80303019.SL	
	Recessed power box 200mm	120mm	
	Textured Black	50041023.TB	
	Textured Silver	50041023.TS	
	Textured white	50041023.TW	
	Ceiling Rose Surf. 120mm	120mm	
	Textured Black	50041024.TB	
	Textured Silver	50041024.TS	
	Textured white	50041024.TW	
	Surface ceiling box 120mm	120mm	
	120mm surface box TB	50041025.TB	
	120mm surface box TS	50041025.TS	
	120mm surface box TW	50041025.TW	
	Surface ceiling box 200mm	200mm	
	200mm surface box TB	50041027.TB	
	200mm surface box TS	50041027.TS	
	200mm surface box TW	50041027.TW	
	Power Cable 0,75	ON/OFF	DALI Push
	Power Cable 1.5m	80303001	80303004
	Power Cable 3m	80303002	80303005
	Power Cable 5m	80303003	80303006