

DESCRIPTION
ORIS 50 VE Surface LINEAR SYSTEM MICROPRISMATIC CRI→80

MOUNTING TYPE	SALIENTE
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Anodized aluminium, Textured Black, Textured White
CONTROL	DALI / Switch Dim, ON/OFF


LED FEATURES

LUMINOUS EFFICIENCY	UP TO 190 lm/W
CRI	CRI→80
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

TECHNICAL DRAWING


ICONOGRAPHY

ORIS 50 VE SURF. LS MICPR
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROL TYPE	LED LUMENS	LUMINAIRE LM	CODE
1130	22.4	AL, TB, TW	3000K	DA, NF	4054	3244	560XX.11P8.830.FI
1130	22.4	AL, TB, TW	4000K	DA, NF	4256	3405	560XX.11P8.840.FI
1410	28	AL, TB, TW	3000K	DA, NF	5068	4054	560XX.14P8.830.FI
1410	28	AL, TB, TW	4000K	DA, NF	5320	4256	560XX.14P8.840.FI
1690	33.6	AL, TB, TW	3000K	DA, NF	6082	4865	560XX.16P8.830.FI
1690	33.6	AL, TB, TW	4000K	DA, NF	6384	5107	560XX.16P8.840.FI
1970	39.2	AL, TB, TW	3000K	DA, NF	7095	5676	560XX.19P8.830.FI
1970	39.2	AL, TB, TW	4000K	DA, NF	7448	5958	560XX.19P8.840.FI
2250	44.8	AL, TB, TW	3000K	DA, NF	8109	6487	560XX.22P8.830.FI
2250	44.8	AL, TB, TW	4000K	DA, NF	8512	6810	560XX.22P8.840.FI
2530	50.4	AL, TB, TW	3000K	DA, NF	9122	7298	560XX.25P8.830.FI
2530	50.4	AL, TB, TW	4000K	DA, NF	9576	7661	560XX.25P8.840.FI
2810	56	AL, TB, TW	3000K	DA, NF	10136	8109	560XX.28P8.830.FI
2810	56	AL, TB, TW	4000K	DA, NF	10640	8512	560XX.28P8.840.FI
3090	61.6	AL, TB, TW	3000K	DA, NF	11150	8920	560XX.30P8.830.FI
3090	61.6	AL, TB, TW	4000K	DA, NF	11704	9363	560XX.30P8.840.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	COLOR TEMP.	CT	FINISHING	FI
DALI / Switch Dim	DA	3000K	30	Anodized aluminium	AL
ON/OFF	NF	4000K	40	Textured Black	TB
				Textured White	TW

ACCESSORIES

Oris 50 Trimless Aces.
Oris 50 Trimless Aces. 8030-1400.2000

Plaster KIT 4 a 5 cm
Plaster KIT 4 a 5 cm 4 - 5cm
 80303058

Plaster KIT 0,7 a 2 cm
Plaster KIT 0,7 a 2 cm 0.7 - 2.1cm
 80303059



Joint ON/OFF ORIS 50
Joint ON/OFF ORIS 50

ON/Off
80303071



Joint DALI ORIS 50
Joint DALI ORIS 50

DALI
80303073