



**DESCRIPTION**

In this section, you will find the product codes for modules designed to create continuous light lines of up to 50 metres, with invisible connections and a quick electrical and mechanical connection system, which simplifies installation and ensures a high-quality finish. It is possible to include 'L', 'T', 'X' or 'Y' connections whilst maintaining the uniformity of the line. It is not possible to combine different diffusers, projectors or lenses in this configuration. For customised solutions, please refer to the ORIS 50 MODULAR section.

<b>MOUNTING TYPE</b>	Encastrar
<b>LIGHT DISTRIBUTION</b>	Direct
<b>POWER SUPPLY</b>	220-230V / 50-60 Hz
<b>WARRANTY</b>	5 Years
<b>FINISHING</b>	Textured Black, Textured White
<b>CONTROL</b>	DALI / Switch Dim, ON/OFF, Tunable White


**LED FEATURES**

<b>LUMINOUS EFFICIENCY</b>	UP TO 155 lm/W
<b>CRI</b>	CRI->90, Tunable White CRI->90
<b>LIFESPAN</b>	50.000 Hours
<b>STEPS MACADAM</b>	3 Steps MacAdam
<b>LUMEN MAINTENANCE</b>	L90/B50
<b>PHOTOBIOLOGICAL RISK</b>	RG1

**TECHNICAL DRAWING**

**ICONOGRAPHY**

**ORIS 50 LS REC. LOW GLARE  
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI->90**

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROL TYPE	LED LUMENS	LUMINAIRE LM	CODE
1130	31	TB, TW	3000K	DA, NF	4501	4276	107XX.11U5.930.FI
1130	31	TB, TW	3000K	DA, NF	4501	4276	107XX.11U8.930.FI
1130	31	TB, TW	4000K	DA, NF	4811	4571	107XX.11U5.940.FI
1130	31	TB, TW	4000K	DA, NF	4811	4571	107XX.11U8.940.FI
1410	38.8	TB, TW	3000K	DA, NF	5626	5345	107XX.14U5.930.FI
1410	38.8	TB, TW	3000K	DA, NF	5626	5345	107XX.14U8.930.FI
1410	38.8	TB, TW	4000K	DA, NF	6014	5713	107XX.14U5.940.FI
1410	38.8	TB, TW	4000K	DA, NF	6014	5713	107XX.14U8.940.FI
1690	46.6	TB, TW	3000K	DA, NF	6751	6414	107XX.16U5.930.FI
1690	46.6	TB, TW	3000K	DA, NF	6751	6414	107XX.16U8.930.FI
1690	46.6	TB, TW	4000K	DA, NF	7217	6856	107XX.16U5.940.FI
1690	46.6	TB, TW	4000K	DA, NF	7217	6856	107XX.16U8.940.FI
1970	54.3	TB, TW	3000K	DA, NF	7876	7483	107XX.19U5.930.FI
1970	54.3	TB, TW	3000K	DA, NF	7876	7483	107XX.19U8.930.FI
1970	54.3	TB, TW	4000K	DA, NF	8420	7999	107XX.19U5.940.FI
1970	54.3	TB, TW	4000K	DA, NF	8420	7999	107XX.19U8.940.FI
2250	62.1	TB, TW	3000K	DA, NF	9002	8552	107XX.22U5.930.FI
2250	62.1	TB, TW	3000K	DA, NF	9002	8552	107XX.22U8.930.FI
2250	62.1	TB, TW	4000K	DA, NF	9622	9141	107XX.22U5.940.FI
2250	62.1	TB, TW	4000K	DA, NF	9622	9141	107XX.22U8.940.FI
2530	69.8	TB, TW	3000K	DA, NF	10127	9620	107XX.25U5.930.FI
2530	69.8	TB, TW	3000K	DA, NF	10127	9620	107XX.25U8.930.FI
2530	69.8	TB, TW	4000K	DA, NF	10825	10284	107XX.25U5.940.FI
2530	69.8	TB, TW	4000K	DA, NF	10825	10284	107XX.25U8.940.FI
2810	77.6	TB, TW	3000K	DA, NF	11252	10689	107XX.28U5.930.FI
2810	77.6	TB, TW	3000K	DA, NF	11252	10689	107XX.28U8.930.FI
2810	77.6	TB, TW	4000K	DA, NF	12028	11427	107XX.28U5.940.FI
2810	77.6	TB, TW	4000K	DA, NF	12028	11427	107XX.28U8.940.FI
3090	85.4	TB, TW	3000K	DA, NF	12377	11758	107XX.30U5.930.FI
3090	85.4	TB, TW	3000K	DA, NF	12377	11758	107XX.30U8.930.FI
3090	85.4	TB, TW	4000K	DA, NF	13231	12569	107XX.30U5.940.FI
3090	85.4	TB, TW	4000K	DA, NF	13231	12569	107XX.30U8.940.FI

**SELECT YOUR PREFERRED  
OPTION**

CONTROL TYPE	XX	COLOR TEMP.	CT	FINISHING	FI
DALI / Switch Dim	DA	3000K	30	Textured Black	TB
ON/OFF	NF	4000K	40	Textured White	TW


**ORIS 50 LS REC. LOW GLARE**  
**PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - Tunable White CRI→90**

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROL TYPE	LED LUMENS	LUMINAIRE LM	CODE
1130	23.9	TB, TW	2700K - 6500K	TU	3463	3289	107XX.11U5.92765.FI
1130	23.9	TB, TW	2700K - 6500K	TU	3463	3289	107XX.11U8.92765.FI
1410	29.9	TB, TW	2700K - 6500K	TU	4328	4112	107XX.14U5.92765.FI
1410	29.9	TB, TW	2700K - 6500K	TU	4328	4112	107XX.14U8.92765.FI
1690	35.8	TB, TW	2700K - 6500K	TU	5194	4934	107XX.16U5.92765.FI
1690	35.8	TB, TW	2700K - 6500K	TU	5194	4934	107XX.16U8.92765.FI
1970	41.8	TB, TW	2700K - 6500K	TU	6060	5757	107XX.19U5.92765.FI
1970	41.8	TB, TW	2700K - 6500K	TU	6060	5757	107XX.19U8.92765.FI
2250	47.8	TB, TW	2700K - 6500K	TU	6925	6579	107XX.22U5.92765.FI
2250	47.8	TB, TW	2700K - 6500K	TU	6925	6579	107XX.22U8.92765.FI
2530	53.7	TB, TW	2700K - 6500K	TU	7791	7401	107XX.25U5.92765.FI
2530	53.7	TB, TW	2700K - 6500K	TU	7791	7401	107XX.25U8.92765.FI

SELECT YOUR PREFERRED  
OPTION

CONTROL TYPE	XX
Tunable White	TU

COLOR TEMP.	CT
2700K - 6500K	92765

FINISHING	FI
Textured Black	TB
Textured White	TW

**ACCESSORIES**


Joint ON/OFF ORIS 50  
Joint ON/OFF ORIS 50

ON/OFF  
80303071



Joint DALI ORIS 50  
Joint DALI ORIS 50

DALI  
80303073