

DESCRIPTION

A space only reveals its true charm with the right lighting. Being aware of this reality, Brilumen presents a LED profiles collection with a 5 Year Warranty, that will help you to create the desired environment. With different wattages, dimensions and mounting types, these profiles can be applied in numerous locations, such as stores, cinemas, museums, galleries, hotels, restaurants, meeting rooms, offices, lounges, etc. With Oris 50mm it's possible to mount light lines up to 3,09 meters without joining, with or without trims, add emergency kits with 1 or 3 hours of autonomy and choose white, black or aluminium as finishing colour. The LED profiles can also be configured in ON-OFF, Dimming 0-10VDC or with the advanced DALI PUSH DIM. Brilumen has also available the IES and LDT files for DIALux projects, providing technical assistance during the lighting project.

MOUNTING	Saliente
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Textured Black, Textured White
CONTROL	CASAMBI, DALI / PUSH Dim, ON/OFF, Tunable White




TECHNICAL DRAWING

LED FEATURES

LUMINOUS EFFICIENCY	UP TO 155 lm/W
CRI	CRI→90, Tunable White CRI→90
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1



ICONOGRAPHY





ORIS 50 LOW GLARE
 PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROLTYPE	LED LUMENS	LUMINAIRE LM	CODE
850	23,3	TB, TW	3000K	CS, DA, NF	3376	3207	5216XX.08U5.930.FI
850	23,3	TB, TW	3000K	CS, DA, NF	3376	3207	5216XX.08U8.930.FI
850	23,3	TB, TW	4000K	CS, DA, NF	3608	3428	5216XX.08U5.940.FI
850	23,3	TB, TW	4000K	CS, DA, NF	3608	3428	5216XX.08U8.940.FI
1130	31	TB, TW	3000K	CS, DA, NF	4501	4276	5216XX.11U5.930.FI
1130	31	TB, TW	3000K	CS, DA, NF	4501	4276	5216XX.11U8.930.FI
1130	31	TB, TW	4000K	CS, DA, NF	4811	4571	5216XX.11U5.940.FI
1130	31	TB, TW	4000K	CS, DA, NF	4811	4571	5216XX.11U8.940.FI
1410	38,8	TB, TW	3000K	CS, DA, NF	5626	5345	5216XX.14U5.930.FI
1410	38,8	TB, TW	3000K	CS, DA, NF	5626	5345	5216XX.14U8.930.FI
1410	38,8	TB, TW	4000K	CS, DA, NF	6014	5713	5216XX.14U5.940.FI
1410	38,8	TB, TW	4000K	CS, DA, NF	6014	5713	5216XX.14U8.940.FI
1690	46,6	TB, TW	3000K	CS, DA, NF	6751	6414	5216XX.16U5.930.FI
1690	46,6	TB, TW	3000K	CS, DA, NF	6751	6414	5216XX.16U8.930.FI
1690	46,6	TB, TW	4000K	CS, DA, NF	7217	6856	5216XX.16U5.940.FI
1690	46,6	TB, TW	4000K	CS, DA, NF	7217	6856	5216XX.16U8.940.FI
1970	54,3	TB, TW	3000K	CS, DA, NF	7876	7483	5216XX.19U5.930.FI
1970	54,3	TB, TW	3000K	CS, DA, NF	7876	7483	5216XX.19U8.930.FI
1970	54,3	TB, TW	4000K	CS, DA, NF	8420	7999	5216XX.19U5.940.FI
1970	54,3	TB, TW	4000K	CS, DA, NF	8420	7999	5216XX.19U8.940.FI
2250	62,1	TB, TW	3000K	CS, DA, NF	9002	8552	5216XX.22U5.930.FI
2250	62,1	TB, TW	3000K	CS, DA, NF	9002	8552	5216XX.22U8.930.FI
2250	62,1	TB, TW	4000K	CS, DA, NF	9622	9141	5216XX.22U5.940.FI
2250	62,1	TB, TW	4000K	CS, DA, NF	9622	9141	5216XX.22U8.940.FI
2530	69,8	TB, TW	3000K	CS, DA, NF	10127	9620	5216XX.25U5.930.FI
2530	69,8	TB, TW	3000K	CS, DA, NF	10127	9620	5216XX.25U8.930.FI
2530	69,8	TB, TW	4000K	CS, DA, NF	10825	10284	5216XX.25U5.940.FI
2530	69,8	TB, TW	4000K	CS, DA, NF	10825	10284	5216XX.25U8.940.FI
2810	77,6	TB, TW	3000K	CS, DA, NF	11252	10689	5216XX.28U5.930.FI
2810	77,6	TB, TW	3000K	CS, DA, NF	11252	10689	5216XX.28U8.930.FI
2810	77,6	TB, TW	4000K	CS, DA, NF	12028	11427	5216XX.28U5.940.FI
2810	77,6	TB, TW	4000K	CS, DA, NF	12028	11427	5216XX.28U8.940.FI
3090	85,4	TB, TW	3000K	CS, DA, NF	12377	11758	5216XX.30U5.930.FI
3090	85,4	TB, TW	3000K	CS, DA, NF	12377	11758	5216XX.30U8.930.FI
3090	85,4	TB, TW	4000K	CS, DA, NF	13231	12569	5216XX.30U5.940.FI
3090	85,4	TB, TW	4000K	CS, DA, NF	13231	12569	5216XX.30U8.940.FI

SELECT YOUR PREFERRED
 OPTION

CONTROLTYPE	XX	COLOR TEMP.	CT	FINISHING	FI
CASAMBI	CS	3000K	30	Textured Black	TB
DALI / PUSH Dim	DA	4000K	40	Textured White	TW
ON/OFF	NF				




ORIS 50 LOW GLARE
 PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - Tunable White CRI→90

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROLTYPE	LED LUMENS	LUMINAIRE LM	CODE
850	17,9	TB, TW	2700K - 6500K	TU	2597	2467	216XX.08U5.92765.FI
850	17,9	TB, TW	2700K - 6500K	TU	2597	2467	216XX.08U8.92765.FI
1130	23,9	TB, TW	2700K - 6500K	TU	3463	3289	216XX.11U5.92765.FI
1130	23,9	TB, TW	2700K - 6500K	TU	3463	3289	216XX.11U8.92765.FI
1410	29,9	TB, TW	2700K - 6500K	TU	4328	4112	216XX.14U5.92765.FI
1410	29,9	TB, TW	2700K - 6500K	TU	4328	4112	216XX.14U8.92765.FI
1690	35,8	TB, TW	2700K - 6500K	TU	5194	4934	216XX.16U5.92765.FI
1690	35,8	TB, TW	2700K - 6500K	TU	5194	4934	216XX.16U8.92765.FI
1970	41,8	TB, TW	2700K - 6500K	TU	6060	5757	216XX.19U5.92765.FI
1970	41,8	TB, TW	2700K - 6500K	TU	6060	5757	216XX.19U8.92765.FI
2250	47,8	TB, TW	2700K - 6500K	TU	6925	6579	216XX.22U5.92765.FI
2250	47,8	TB, TW	2700K - 6500K	TU	6925	6579	216XX.22U8.92765.FI
2530	53,7	TB, TW	2700K - 6500K	TU	7791	7401	216XX.25U5.92765.FI
2530	53,7	TB, TW	2700K - 6500K	TU	7791	7401	216XX.25U8.92765.FI


SELECT YOUR PREFERRED
 OPTION

CONTROLTYPE	XX	COLOR TEMP.	CT	FINISHING	FI
Tunable White	TU	2700K - 6500K	92765	Textured Black	TB
				Textured White	TW

ACCESSORIES



Oris 50 Trimless Aces. -
 Oris 50 Trimless Aces. 8030-1400.2000



Plaster KIT 4 a 5 cm
Plaster KIT 4 a 5 cm

4 - 5cm
80303058



Plaster KIT 0,7 a 2 cm
Plaster KIT 0,7 a 2 cm

0.7 - 2.1cm
80303059