

DESCRIPTION

Technical lighting is increasingly considered when designing spaces and the purpose for which they are intended, because each place has its own specificity and lighting needs.

The Wall Washer from the ORIS Plus range, with adapter for 230V universal track, was developed precisely to respond to one of these shortcomings, that of sweeping the wall with uniform and efficient light to highlight the products exhibited there.


MOUNTING TYPE	Uni Track
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Textured Black, Textured White
CONTROL	DALI / Switch Dim, ON/OFF




LED FEATURES

LUMINOUS EFFICIENCY	UP TO 92 lm/W
CRI	CRI->90
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

TECHNICAL DRAWING



ICONOGRAPHY



**ORIS+ EFFI. WALL WASHER
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI->90**

LENGTH	POWER	FINISHING	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
290	12.8	TB, TW	DA, NF	U3, U4	1096	978	3000K	283XX.02U3.930.FI
290	12.8	TB, TW	DA, NF	U3, U4	1096	978	3000K	283XX.02U4.930.FI
290	12.8	TB, TW	DA, NF	U3, U4	1178	1051	4000K	283XX.02U3.940.FI
290	12.8	TB, TW	DA, NF	U3, U4	1178	1051	4000K	283XX.02U4.940.FI
580	25.5	TB, TW	DA, NF	U3, U4	2191	1956	3000K	283XX.05U3.930.FI
580	25.5	TB, TW	DA, NF	U3, U4	2191	1956	3000K	283XX.05U4.930.FI
580	25.5	TB, TW	DA, NF	U3, U4	2356	2103	4000K	283XX.05U3.940.FI
580	25.5	TB, TW	DA, NF	U3, U4	2356	2103	4000K	283XX.05U4.940.FI
850	38.3	TB, TW	DA, NF	U3, U4	3287	2934	3000K	283XX.08U3.930.FI
850	38.3	TB, TW	DA, NF	U3, U4	3287	2934	3000K	283XX.08U4.930.FI
850	38.3	TB, TW	DA, NF	U3, U4	3533	3154	4000K	283XX.08U3.940.FI
850	38.3	TB, TW	DA, NF	U3, U4	3533	3154	4000K	283XX.08U4.940.FI
1130	51.1	TB, TW	DA, NF	U3, U4	4382	3912	3000K	283XX.11U3.930.FI
1130	51.1	TB, TW	DA, NF	U3, U4	4382	3912	3000K	283XX.11U4.930.FI
1130	51.1	TB, TW	DA, NF	U3, U4	4711	4206	4000K	283XX.11U3.940.FI
1130	51.1	TB, TW	DA, NF	U3, U4	4711	4206	4000K	283XX.11U4.940.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	FINISHING	FI	BEAM ANGLE	BA
DALI / Switch Dim	DA	Textured Black	TB	30°	U3
ON/OFF	NF	Textured White	TW	45°	U4

ACCESSORIES

	Track ON/OFF Susp./Surf.	
	ON/OFF Track 1m Black	UP1459429-1
	ON/OFF Track 1m White	UP1459102-1
	ON/OFF Track 2m Black	UP1459429
	ON/OFF Track 2m White	UP1459102
	Track DALI Susp./Surf.	
	DALI Track 1m Black	UP1459439-1
	DALI Track 1m White	UP1459107-1
	DALI Track 2m Black	UP1459439
	DALI Track 2m White	UP1459107
	Recess. Track ON/OFF	
	ON/OFF Rec. Track 1m Bl	UP1459312-1



ON/OFF Rec. Track 1m WH
ON/OFF Rec. Track 2m BL
ON/OFF Rec. Track 2m WH

UP1459112-1
UP1459312
UP1459112



Recessed Track DALI
DALI Rec. Track 1m BL
DALI Rec. Track 1m WH
DALI Rec. Track 2m BL
DALI Rec. Track 2m WH

UP1459317-1
UP1459117-1
UP1459317
UP1459117