

DESCRIPTION


ORIS Plus High Performance is a solution that can be used to illuminate large spaces, in continuous lines up to 15 m, such as supermarkets, large retail stores and even industrial environments. It is possible to incorporate lenses to control the beam angle of the lighting fixture, which allows changing the light distribution according to the needs of the place. In this version, high efficiency is also highlighted, with LEDs up to 168lm/W in a single linear profile of 3370mm. Smart Lighting options with motion and brightness sensors are also available. Oris Plus is an upgrade of our ORIS 50mm. It is a linear LED light with 53,4mm width and 73mm height. These new dimensions allow to accommodate the batteries of the emergency lighting function inside the product. Or, alternatively, it provides space for the electrical cables needed to mount continuous light lines in large spaces. Various sizes up to 3370mm seamless are available. The ORIS Plus Linear LED Light has an option in which the screws are completely hidden. The finishes can be in a high quality textured "sablé" white or black or in natural anodized aluminium. The built-in light technology is high quality, Tridonic with 5 year warranty.



MOUNTING TYPE	Surface
LIGHT DISTRIBUTION	Directa
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Anodized aluminium, Textured Black, Textured White
CONTROL	1-10V, DALI / Switch Dim, ON/OFF

LED FEATURES

LUMINOUS EFFICIENCY	UP TO 186 lm/W
CRI	CRI>80
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY

ORIS+ HP OPAL
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI>80

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROL TYPE	LED LUMENS	LUMINAIRE LM	CODE
1130	48	AL, TB, TW	4000K	1V, DA, NF	8798	6507	156XX.1109.840.FI
1130	48	AL, TB, TW	5000K	1V, DA, NF	8911	6590	156XX.1109.850.FI
1690	72	AL, TB, TW	4000K	1V, DA, NF	13197	9675	156XX.1609.840.FI
1690	72	AL, TB, TW	5000K	1V, DA, NF	13367	9800	156XX.1609.850.FI
2250	96	AL, TB, TW	4000K	1V, DA, NF	17596	13014	156XX.2209.840.FI
2250	96	AL, TB, TW	5000K	1V, DA, NF	17822	13180	156XX.2209.850.FI
2810	120	AL, TB, TW	4000K	1V, DA, NF	21995	16182	156XX.2809.840.FI
2810	120	AL, TB, TW	5000K	1V, DA, NF	22278	16390	156XX.2809.850.FI
3370	144	AL, TB, TW	4000K	1V, DA, NF	26394	19350	156XX.3309.840.FI
3370	144	AL, TB, TW	5000K	1V, DA, NF	26734	19600	156XX.3309.850.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	COLOR TEMP.	CT	FINISHING	FI
1-10V	1V	4000K	40	Anodized aluminium	AL
DALI / Switch Dim	DA	5000K	50	Textured Black	TB
ON/OFF	NF			Textured White	TW

ACCESSORIES

CASAMBI - DALI Interface
CASAMBI - DALI Interface
CASAMBI
8030-2590