

DESCRIPTION

ORIS Plus High Performance is a solution that can be used to illuminate large spaces, in continuous lines up to 15 m, such as supermarkets, large retail stores and even industrial environments. It is possible to incorporate lenses to control the beam angle of the lighting fixture, which allows changing the light distribution according to the needs of the place. In this version, high efficiency is also highlighted, with LEDs up to 205lm/W in a single linear profile of 3370mm. Smart Lighting options with motion and brightness sensors are also available. Oris Plus is an upgrade of our ORIS 50mm. It is a linear LED light with 53.4mm width and 73mm height. These new dimensions allow to accommodate the batteries of the emergency lighting function inside the product. Or, alternatively, it provides space for the electrical cables needed to mount continuous light lines in large spaces. Various sizes up to 3370mm seamless are available. The ORIS Plus Linear LED Light has an option in which the screws are completely hidden. The finishes can be in a high quality textured "sablé" white or black or in natural anodized aluminium. The built-in light technology is high quality, Tridonic with 5 year warranty.

MOUNTING TYPE	Surface
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Anodized aluminium, Textured Black, Textured White
CONTROL	1-10V, DALI / Switch Dim, ON/OFF




TECHNICAL DRAWING



LED FEATURES

LUMINOUS EFFICIENCY	UP TO 206 lm/W
CRI	CRI→80
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY



ORIS+ HP PRISMATIC PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROL TYPE	LED LUMENS	LUMINAIRE LM	CODE
1130	33	AL, TB, TW	4000K	1V, DA, NF	6679	5372	156XX.11P8.840.FI
1130	33	AL, TB, TW	5000K	1V, DA, NF	6765	5442	156XX.11P8.850.FI
1690	49.5	AL, TB, TW	4000K	1V, DA, NF	10019	8091	156XX.16P8.840.FI
1690	49.5	AL, TB, TW	5000K	1V, DA, NF	10148	8195	156XX.16P8.850.FI
2250	66	AL, TB, TW	4000K	1V, DA, NF	13358	10744	156XX.22P8.840.FI
2250	66	AL, TB, TW	5000K	1V, DA, NF	13530	10884	156XX.22P8.850.FI
2810	82.5	AL, TB, TW	4000K	1V, DA, NF	16698	13463	156XX.28P8.840.FI
2810	82.5	AL, TB, TW	5000K	1V, DA, NF	16913	13637	156XX.28P8.850.FI
3370	99	AL, TB, TW	4000K	1V, DA, NF	20038	16182	156XX.33P8.840.FI
3370	99	AL, TB, TW	5000K	1V, DA, NF	20296	16390	156XX.33P8.850.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX
1-10V	1V
DALI / Switch Dim	DA
ON/OFF	NF

COLOR TEMP.	CT
4000K	40
5000K	50

FINISHING	FI
Anodized aluminium	AL
Textured Black	TB
Textured White	TW

ACCESSORIES



CASAMBI - DALI Interface
CASAMBI - DALI Interface

CASAMBI
8030-2590