

DESCRIPTION

ORIS Plus High Performance is a solution that can be used to illuminate large spaces, in continuous lines up to 15 m, such as supermarkets, large retail stores and even industrial environments. It is possible to incorporate lenses to control the beam angle of the lighting fixture, which allows changing the light distribution according to the needs of the place. In this version, high efficiency is also highlighted, with LEDs up to 205lm/W in a single linear profile of 3370mm. Smart Lighting options with motion and brightness sensors are also available. Oris Plus is an upgrade of our ORIS 50mm. It is a linear LED light with 53,4mm width and 73mm height. These new dimensions allow to accommodate the batteries of the emergency lighting function inside the product. Or, alternatively, it provides space for the electrical cables needed to mount continuous light lines in large spaces. Various sizes up to 3370mm seamless are available. The ORIS Plus Linear LED Light has an option in which the screws are completely hidden. The finishes can be in a high quality textured "sablé" white or black or in natural anodized aluminium. The built-in light technology is high quality, Tridonic with 5 year warranty.




MOUNTING	Surface
LIGHT DISTRIBUTION	Directa
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Anodized aluminium, Textured Black, Textured White
CONTROL	1-10V, DALI / PUSH Dim, ON/OFF

TECHNICAL DRAWING

LED FEATURES

LUMINOUS EFFICIENCY	UP TO 206 lm/W
CRI	CRI→80
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY

**ORIS+ HP PRISMATIC
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80**

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROLTYPE	LED LUMENS	LUMINAIRE LM	CODE
1130	33	AL, TB, TW	4000K	1V, DA, NF	6679	5372	156XX.11P8.840.FI
1130	33	AL, TB, TW	5000K	1V, DA, NF	6765	5442	156XX.11P8.850.FI
1690	49,5	AL, TB, TW	4000K	1V, DA, NF	10019	8091	156XX.16P8.840.FI
1690	49,5	AL, TB, TW	5000K	1V, DA, NF	10148	8195	156XX.16P8.850.FI
2250	66	AL, TB, TW	4000K	1V, DA, NF	13358	10744	156XX.22P8.840.FI
2250	66	AL, TB, TW	5000K	1V, DA, NF	13530	10884	156XX.22P8.850.FI
2810	82,5	AL, TB, TW	4000K	1V, DA, NF	16698	13463	156XX.28P8.840.FI
2810	82,5	AL, TB, TW	5000K	1V, DA, NF	16913	13637	156XX.28P8.850.FI
3370	99	AL, TB, TW	4000K	1V, DA, NF	20038	16182	156XX.33P8.840.FI
3370	99	AL, TB, TW	5000K	1V, DA, NF	20296	16390	156XX.33P8.850.FI

**SELECT YOUR PREFERRED
OPTION**

CONTROLTYPE	XX	COLOR TEMP.	CT	FINISHING	FI
1-10V	1V	4000K	40	Anodized aluminium	AL
DALI / PUSH Dim	DA	5000K	50	Textured Black	TB
ON/OFF	NF			Textured White	TW

ACCESSORIES


CASAMBI - DALI Interface
CASAMBI - DALI Interface

CASAMBI
8030-2590