

DESCRIPTION

ORIS Plus High Performance is a solution that can be used to illuminate large spaces, in continuous lines up to 15 m, such as supermarkets, large retail stores and even industrial environments. It is possible to incorporate lenses to control the beam angle of the lighting fixture, which allows changing the light distribution according to the needs of the place. In this version, high efficiency is also highlighted, with LEDs up to 168lm/W in a single linear profile of 3370mm. Smart Lighting options with motion and brightness sensors are also available. Or is Plus is an upgrade of our ORIS 50mm. It is a linear LED light with 53,4mm width and 73mm height. These new dimensions allow to accommodate the batteries of the emergency lighting function inside the product. Or, alternatively, it provides space for the electrical cables needed to mount continuous light lines in large spaces. Various sizes up to 3370mm seamless are available. The ORIS Plus Linear LED Light has an option in which the screws are completely hidden. The finishes can be in a high quality textured "sable" white or black or in natural anodized aluminium. The built-in light technology is high quality, Tridonic with 5 year warranty.

MOUNTING TYPE Suspension LIGHT DISTRIBUTION Direct 220-230V / 50-60 Hz **POWER SUPPLY**

WARRANTY 5 Years

FINISHING Anodized aluminium, Textured Black, Textured White

CONTROL 1-10V, DALI / Switch Dim, ON/OFF

LED FEATURES

LUMINOUS EFFICIENCY CRI→80 LIFESPAN 50.000 Hours STEPS MACADAM L90/B50 **LUMEN MAINTENANCE** PHOTOBIOLOGICAL RISK RG1

UP TO 186 lm/W 3 Steps MacAdam

ICONOGRAPHY





ORIS+ HP OPAL

PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80

1130	48	AL, TB, TW	4000K	1V, DA, NF	8798	6507	157XX.1109.840.FI
1130	48	AL, TB, TW	5000K	1V, DA, NF	8911	6590	157XX.1109.850.FI
1690	72	AL, TB, TW	4000K	1V, DA, NF	13197	9675	157XX.1609.840.FI
1690	72	AL, TB, TW	5000K	1V, DA, NF	13367	9800	157XX.1609.850.FI
2250	96	AL, TB, TW	4000K	1V, DA, NF	17596	13014	157XX.2209.840.FI
2250	96	AL, TB, TW	5000K	1V, DA, NF	17822	13180	157XX.2209.850.FI
2810	120	AL, TB, TW	4000K	1V, DA, NF	21995	16182	157XX.2809.840.FI
2810	120	AL, TB, TW	5000K	1V, DA, NF	22278	16390	157XX.2809.850.FI
3370	144	AL, TB, TW	4000K	1V, DA, NF	26394	19350	157XX.3309.840.FI
3370	144	AL, TB, TW	5000K	1V, DA, NF	26734	19600	157XX.3309.850.FI

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX
1-10V	1V
DALI / Switch Dim	DA
ON/OFF	NF

COLOR TEMP.	
4000K	40
5000K	50

Anodized aluminium	AL
Textured Black	TB
Textured White	TW

ACCESSORIES



	Ceiling Rose Surface		ck
	Ceiling Rose Surface	80303021.TW	
-	Ceiling Rose Surface	80303021.TS	
	Ceiling Rose Surface	80303021.TB	

TECHNICAL DRAWING







Power Cable 0,75	ON/Off	DALI Push	
Power Cable 1.5m	80303001		
Power Cable 1.5m	80303004		
Power Cable 3m	80303002		
Power Cable 3m	80303005		
Power Cable 5m	80303003		
Power Cable 5m	80303006		
Ceiling Rose Recessed			
Ceiling Rose Recessed	80303020.TW		
Ceiling Rose Recessed	80303020.TS		
Ceiling Rose Recessed	80303020.TB		



CASAMBI - DALI Interface	CASAMBI
CASAMBI - DALI Interface	8030-2590