

DESCRIPTION


ORIS Plus High Performance is a solution that can be used to illuminate large spaces, in continuous lines up to 15 m, such as supermarkets, large retail stores and even industrial environments. It is possible to incorporate lenses to control the beam angle of the lighting fixture, which allows changing the light distribution according to the needs of the place. In this version, high efficiency is also highlighted, with LEDs up to 168lm/W in a single linear profile of 3370mm. Smart Lighting options with motion and brightness sensors are also available. Oris Plus is an upgrade of our ORIS 50mm. It is a linear LED light with 53.4mm width and 73mm height. These new dimensions allow to accommodate the batteries of the emergency lighting function inside the product. Or, alternatively, it provides space for the electrical cables needed to mount continuous light lines in large spaces. Various sizes up to 3370mm seamless are available. The ORIS Plus Linear LED Light has an option in which the screws are completely hidden. The finishes can be in a high quality textured "sablé" white or black or in natural anodized aluminium. The built-in light technology is high quality, Tridonic with 5 year warranty.

MOUNTING TYPE	Suspension
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Anodized aluminium, Textured Black, Textured White
CONTROL	1-10V, DALI / Switch Dim, ON/OFF

LED FEATURES

LUMINOUS EFFICIENCY	UP TO 186 lm/W
CRI	CRI→80
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBILOGICAL RISK	RG1

ICONOGRAPHY

ORIS+ HP OPAL
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROL TYPE	LED LUMENS	LUMINAIRE LM	CODE
1130	48	AL, TB, TW	4000K	1V, DA, NF	8798	6507	157XX.1109.840.FI
1130	48	AL, TB, TW	5000K	1V, DA, NF	8911	6590	157XX.1109.850.FI
1690	72	AL, TB, TW	4000K	1V, DA, NF	13197	9675	157XX.1609.840.FI
1690	72	AL, TB, TW	5000K	1V, DA, NF	13367	9800	157XX.1609.850.FI
2250	96	AL, TB, TW	4000K	1V, DA, NF	17596	13014	157XX.2209.840.FI
2250	96	AL, TB, TW	5000K	1V, DA, NF	17822	13180	157XX.2209.850.FI
2810	120	AL, TB, TW	4000K	1V, DA, NF	21995	16182	157XX.2809.840.FI
2810	120	AL, TB, TW	5000K	1V, DA, NF	22278	16390	157XX.2809.850.FI
3370	144	AL, TB, TW	4000K	1V, DA, NF	26394	19350	157XX.3309.840.FI
3370	144	AL, TB, TW	5000K	1V, DA, NF	26734	19600	157XX.3309.850.FI

SELECT YOUR PREFERRED
OPTION

CONTROL TYPE	XX
1-10V	1V
DALI / Switch Dim	DA
ON/OFF	NF

COLOR TEMP.	CT
4000K	40
5000K	50

FINISHING	FI
Anodized aluminium	AL
Textured Black	TB
Textured White	TW

ACCESSORIES



Suspension Kit	Silver
Suspension kit 1,5m (1un)	80303017.SL
Suspension kit 3 m (1un)	80303018.SL
Suspension kit 5 m (1un)	80303019.SL



Ceiling Rose Surface	Textured White	Textured Silver	Textured Black
Ceiling Rose Surface	80303021.TW		
Ceiling Rose Surface	80303021.TS		
Ceiling Rose Surface	80303021.TB		



TECHNICAL DRAWING





Power Cable 0,75	ON/Off	DALI Push
Power Cable 1.5m	80303001	
Power Cable 1.5m	80303004	
Power Cable 3m	80303002	
Power Cable 3m	80303005	
Power Cable 5m	80303003	
Power Cable 5m	80303006	

	Ceiling Rose Recessed	Textured White	Textured Silver	Textured Black
	Ceiling Rose Recessed	80303020.TW		
	Ceiling Rose Recessed	80303020.TS		
	Ceiling Rose Recessed	80303020.TB		



CASAMBI - DALI Interface	CASAMBI
CASAMBI - DALI Interface	8030-2590