


DESCRIPTION


With this version of the ORIS SLIM PRO COMBI, it is possible to obtain reduced size light lines while spreading simultaneously direct, thus offering greater freedom for those who design the lighting for a space.

MOUNTING	Saliente
LIGHT DISTRIBUTION	Directa
POWER SUPPLY	220-240V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Anodized aluminium, Textured Black, Textured Silver, Textured White
CONTROL	DALI / PUSH Dim, ON/OFF


LED FEATURES

LUMINOUS EFFICIENCY	UP TO 153 lm/W
CRI	CRI->90
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

TECHNICAL DRAWING

ICONOGRAPHY

ORIS S.P.COMBI OP+L3
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI->90

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROLTYPE	LED LUMENS	LUMINAIRE LM	CODE
1420	22,9	TB, TS, TW	3000K	DA, NF	3460	2602	484XX.1409.930.FI
1420	22,9	TB, TS, TW	4000K	DA, NF	3460	2602	484XX.1409.940.FI
1700	28	TB, TS, TW	3000K	DA, NF	4248	3135	484XX.1709.930.FI
1700	28	TB, TS, TW	4000K	DA, NF	4248	3135	484XX.1709.940.FI
1980	33,1	TB, TS, TW	3000K	DA, NF	5036	3668	484XX.1909.930.FI
1980	33,1	TB, TS, TW	4000K	DA, NF	5036	3668	484XX.1909.940.FI
2260	38,2	TB, TS, TW	3000K	DA, NF	5824	4199	484XX.2209.930.FI
2260	38,2	TB, TS, TW	4000K	DA, NF	5824	4199	484XX.2209.940.FI
2540	43,4	TB, TS, TW	3000K	DA, NF	6611	4732	484XX.2509.930.FI
2540	43,4	TB, TS, TW	4000K	DA, NF	6611	4732	484XX.2509.940.FI

SELECT YOUR PREFERRED OPTION

CONTROLTYPE	XX	COLOR TEMP.	CT	FINISHING	FI
DALI / PUSH Dim	DA	3000K	30	Textured Black	TB
ON/OFF	NF	4000K	40	Textured Silver	TS
				Textured White	TW

ACCESSORIES


CASAMBI - DALI Interface
 CASAMBI - DALI Interface

CASAMBI
 8030-2590