


**DESCRIPTION**

With this version of the ORIS SLIM PRO COMBI, it is possible to obtain reduced size light lines while spreading simultaneously direct, thus offering greater freedom for those who design the lighting for a space.

<b>MOUNTING</b>	Suspension
<b>LIGHT DISTRIBUTION</b>	Directa
<b>POWER SUPPLY</b>	220-240V / 50-60 Hz
<b>WARRANTY</b>	5 Years
<b>FINISHING</b>	Anodized aluminium, Textured Black, Textured Silver, Textured White
<b>CONTROL</b>	DALI / PUSH Dim, ON/OFF



**LED FEATURES**

<b>LUMINOUS EFFICIENCY</b>	UP TO 153 lm/W
<b>CRI</b>	CRI->90
<b>LIFESPAN</b>	50.000 Hours
<b>STEPS MACADAM</b>	3 Steps MacAdam
<b>LUMEN MAINTENANCE</b>	L90/B50
<b>PHOTOBIOLOGICAL RISK</b>	RG1

**TECHNICAL DRAWING**



**ICONOGRAPHY**







**ORIS S.P.COMBI OP+L3**  
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI->90

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROLTYPE	LED LUMENS	LUMINAIRE LM	CODE
1420	22,9	TB, TS, TW	3000K	DA, NF	3460	2602	482XX.1409.930.FI
1420	22,9	TB, TS, TW	4000K	DA, NF	3460	2602	482XX.1409.940.FI
1700	28	TB, TS, TW	3000K	DA, NF	4248	3135	482XX.1709.930.FI
1700	28	TB, TS, TW	4000K	DA, NF	4248	3135	482XX.1709.940.FI
1980	33,1	TB, TS, TW	3000K	DA, NF	5036	3668	482XX.1909.930.FI
1980	33,1	TB, TS, TW	4000K	DA, NF	5036	3668	482XX.1909.940.FI
2260	38,2	TB, TS, TW	3000K	DA, NF	5824	4199	482XX.2209.930.FI
2260	38,2	TB, TS, TW	4000K	DA, NF	5824	4199	482XX.2209.940.FI
2540	43,4	TB, TS, TW	3000K	DA, NF	6611	4732	482XX.2509.930.FI
2540	43,4	TB, TS, TW	4000K	DA, NF	6611	4732	482XX.2509.940.FI

**SELECT YOUR PREFERRED OPTION**

CONTROLTYPE	XX	COLOR TEMP.	CT	FINISHING	FI
DALI / PUSH Dim	DA	3000K	30	Textured Black	TB
ON/OFF	NF	4000K	40	Textured Silver	TS
				Textured White	TW

**ACCESSORIES**

	Suspension Kit Suspension kit 1,5m (1un) Suspension kit 3 m (1un) Suspension kit 5 m (1un)	Silver 80303017.SL 80303018.SL 80303019.SL		
	Ceiling Rose Recessed Ceiling Rose Recessed	Textured White 80303020.TW	Textured Silver 80303020.TS	Textured Black 80303020.TB
	Ceiling Rose Surface Ceiling Rose Surface	Textured White 80303021.TW	Textured Silver 80303021.TS	Textured Black 80303021.TB
	Power Cable 0,75 Power Cable 1.5m Power Cable 3m	ON/OFF 80303001 80303002	DALI Push 80303004 80303005	

Power Cable 5m

80303003

80303006



CASAMBI - DALI Interface  
CASAMBI - DALI Interface

CASAMBI  
8030-2590