

**DESCRIPTION**

Oris SlimPro The reduced dimensions of only 26 mm in width make this luminaire slim and distinctive. With a minimalist design, this light fixture was designed for refined spaces, where lighting is discreet, but efficient and with a high CRI. Oris SlimPro has the options of direct/indirect light, opal and prismatic diffuser, different beam angles, low glare reflectors and lenses, and comes in versions adaptable for ceilings, surface or walls. Specially developed to meet the requirements of architects, who are looking for thin and modular lighting fixtures. With SlimPro, it's possible to mount slim lines of light up to 3,375m without the need of joints. A selection of finishing colours starting from white, black to silver. The LED profiles come as well with the options to be configured in ON-OFF, DALI or CASAMBI.


<b>MOUNTING</b>	Surface
<b>LIGHT DISTRIBUTION</b>	Directa
<b>POWER SUPPLY</b>	220-230V / 50-60 Hz
<b>WARRANTY</b>	5 Years
<b>FINISHING</b>	Textured Black, Textured Silver, Textured White
<b>CONTROL</b>	DALI / PUSH Dim, ON/OFF




**TECHNICAL DRAWING**

**LED FEATURES**

<b>LUMINOUS EFFICIENCY</b>	UP TO 195 lm/W
<b>CRI</b>	CRI→90
<b>LIFESPAN</b>	50.000 Hours
<b>STEPS MACADAM</b>	3 Steps MacAdam
<b>LUMEN MAINTENANCE</b>	L90/B50
<b>PHOTOBIOLOGICAL RISK</b>	RG1



**ICONOGRAPHY**



**ORIS SLIM PRO LOW GLARE**  
**PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90**

LENGTH	POWER	FINISHING	COLOR TEMP.	CONTROLTYPE	LED LUMENS	LUMINAIRE LM	CODE
570	7,8	TB, TS, TW	3000K	DA, NF	1482	1305	5247XX.05U6.930.FI
570	7,8	TB, TS, TW	4000K	DA, NF	1529	1347	5247XX.05U6.940.FI
850	11,8	TB, TS, TW	3000K	DA, NF	2223	1958	5247XX.08U6.930.FI
850	11,8	TB, TS, TW	4000K	DA, NF	2293	2020	5247XX.08U6.940.FI
1130	15,7	TB, TS, TW	3000K	DA, NF	2964	2611	5247XX.11U6.930.FI
1130	15,7	TB, TS, TW	4000K	DA, NF	3058	2694	5247XX.11U6.940.FI
1410	19,6	TB, TS, TW	3000K	DA, NF	3704	3264	5247XX.14U6.930.FI
1410	19,6	TB, TS, TW	4000K	DA, NF	3822	3367	5247XX.14U6.940.FI
1690	23,5	TB, TS, TW	3000K	DA, NF	4445	3916	5247XX.16U6.930.FI
1690	23,5	TB, TS, TW	4000K	DA, NF	4586	4041	5247XX.16U6.940.FI
1970	27,4	TB, TS, TW	3000K	DA, NF	5186	4569	5247XX.19U6.930.FI
1970	27,4	TB, TS, TW	4000K	DA, NF	5351	4714	5247XX.19U6.940.FI
2250	31,4	TB, TS, TW	3000K	DA, NF	5927	5222	5247XX.22U6.930.FI
2250	31,4	TB, TS, TW	4000K	DA, NF	6115	5387	5247XX.22U6.940.FI
2530	35,3	TB, TS, TW	3000K	DA, NF	6668	5874	5247XX.25U6.930.FI
2530	35,3	TB, TS, TW	4000K	DA, NF	6880	6061	5247XX.25U6.940.FI
2810	39,2	TB, TS, TW	3000K	DA, NF	7409	6527	5247XX.28U6.930.FI
2810	39,2	TB, TS, TW	4000K	DA, NF	7644	6734	5247XX.28U6.940.FI
3090	43,1	TB, TS, TW	3000K	DA, NF	8150	7180	5247XX.30U6.930.FI
3090	43,1	TB, TS, TW	4000K	DA, NF	8408	7408	5247XX.30U6.940.FI
3370	47	TB, TS, TW	3000K	DA, NF	8891	7833	5247XX.33U6.930.FI
3370	47	TB, TS, TW	4000K	DA, NF	9173	8081	5247XX.33U6.940.FI

SELECT YOUR PREFERRED OPTION

CONTROLTYPE	XX	COLOR TEMP.	CT	FINISHING	FI
DALI / PUSH Dim	DA	3000K	30	Textured Black	TB
ON/OFF	NF	4000K	40	Textured Silver	TS
				Textured White	TW

**ACCESSORIES**

