


**DESCRIPTION**


The PROLINER is a magical line of light. Consisting of particularly narrow modules, it allows the creation of a versatile light line in a low-voltage magnetic rail. It is composed of 3 different light modules. A module with opal or prismatic polycarbonate diffuser, a module with a low glare reflector, and a module with a 30° lens to control the beam angle. By combining these modules, the PROLINER draws a thin and elegant light line through its opal polycarbonate diffuser. In the low glare version, the light is emitted in a recessed way, protecting the eyes and highlighting the more reliably colours of the lightened objects. The option with a 30° lens allows creating the best light distribution according to the space and to focus the light on specific points. The magnetic application allows the greater flexibility of light configuration in space, and can be reconfigured with complete freedom, without resorting to specialized technicians or special tools. The magnetic rails where the PROLINER is installed are low voltage (48V). PROLINER has been specially designed to be combined with APALIS or ROSS. These discreet application luminaires in magnetic rails are specially intended for lighting projects where the reconfiguration of spaces and objects may occur regularly, such as, stores, art galleries, museums, exhibition venues, etc... Together, these products can make your lighting project a truly magical space.



<b>MOUNTING</b>	Magnetic
<b>LIGHT DISTRIBUTION</b>	Directa
<b>POWER SUPPLY</b>	48V / TRACK
<b>WARRANTY</b>	5 Years
<b>FINISHING</b>	Black, White
<b>CONTROL</b>	CASAMBI, DALI, ON/OFF

**TECHNICAL DRAWING**

**LED FEATURES**

<b>LUMINOUS EFFICIENCY</b>	UP TO 143 lm/W
<b>CRI</b>	CRI->90
<b>LIFESPAN</b>	50.000 Hours
<b>STEPS MACADAM</b>	3 Steps MacAdam
<b>LUMEN MAINTENANCE</b>	L90/B50
<b>PHOTOBIOLOGICAL RISK</b>	RG1

**ICONOGRAPHY**


**PROLINER LENS 48V**  
**PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI->90**

LENGTH	POWER	FINISHING	CONTROLTYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
570	8,2	BL, WH	CS, DL, NF	30	1109	1017	3000K	153XX.05L3.9BA.FI
570	8,2	BL, WH	CS, DL, NF	30	1164	1068	4000K	153XX.05L3.940.FI
1130	16,4	BL, WH	CS, DL, NF	30	2218	2033	3000K	153XX.11L3.9BA.FI
1130	16,4	BL, WH	CS, DL, NF	30	2328	2135	4000K	153XX.11L3.940.FI

**SELECT YOUR PREFERRED OPTION**

CONTROLTYPE	XX	FINISHING	FI	BEAM ANGLE	BA
CASAMBI	CS	Black	BL	30°	30
DALI	DL	White	WH		
ON/OFF	NF				

**ACCESSORIES**

	<b>BT1E - Track 48V EVO</b> Track 48V EVO 1M Track 48V EVO 2M	White      Black 3080-0175E.WH   3080-0175E.BL 3080-0176E.WH   3080-0176E.BL
	<b>BT2E - Track 48V EVO</b> Track 48V EVO 1M Track 48V EVO 2M	White      Black 3080-0177E.WH   3080-0177E.BL 3080-0178E.WH   3080-0178E.BL
	<b>TK3 Magnetic Track</b> Magnetic Track 48V 1M Magnetic Track 48V 2M	White      Black 3080-0205.WH   3080-0205.BL 3080-0206.WH   3080-0206.BL



TK5E - Track 48V EVO  
Track 48V EVO 1M  
Track 48V EVO 2M

White	Black
3080-0250E.WH	3080-0250E.BL
3080-0251E.WH	3080-0251E.BL




TK9E - Track 48V EVO  
Track 48V EVO 1M  
Track 48V EVO 2M

White	Black
3080-0211E.WH	3080-0211E.BL
3080-0212E.WH	3080-0212E.BL


**PHOTOMETRIC DATA**

**POLAR DIAGRAM AND LUMINOUS FLUX - LENS Titulo**



1m	Ø3,3m	1.382,5 lx
2m	Ø6,5m	345,6 lx
3m	Ø9,8m	153,6 lx
4m	Ø13m	86,4 lx
5m	Ø16,3m	55,3 lx
6m	Ø19,5m	38,4 lx

ØDIE 24W / 1000K CRI90 1120MM



1m	Ø3,3m	1.382,5 lx
2m	Ø6,5m	345,6 lx
3m	Ø9,8m	153,6 lx
4m	Ø13m	86,4 lx
5m	Ø16,3m	55,3 lx
6m	Ø19,5m	38,4 lx

ØDIE 24W / 1000K CRI90 1120MM