


DESCRIPTION

The PROLINER is a magical line of light. Consisting of particularly narrow modules, it allows the creation of a versatile light line in a low-voltage magnetic rail. It is composed of 3 different light modules. A module with opal or prismatic polycarbonate diffuser, a module with a low glare reflector, and a module with a 60° lens to control the beam angle. By combining these modules, the PROLINER draws a thin and elegant light line through its opal polycarbonate diffuser. In the low glare version, the light is emitted in a recessed way, protecting the eyes and highlighting the more reliably colours of the lightened objects. The option with a 60° lens allows creating the best light distribution according to the space and to focus the light on specific points. The magnetic application allows the greater flexibility of light configuration in space, and can be reconfigured with complete freedom, without resorting to specialized technicians or special tools. The magnetic rails where the PROLINER is installed are low voltage (48V). PROLINER has been specially designed to be combined with APALIS or ROSS. These discreet application luminaires in magnetic rails are specially intended for lighting projects where the reconfiguration of spaces and objects may occur regularly, such as, stores, art galleries, museums, exhibition venues, etc... Together, these products can make your lighting project a truly magical space.



LIGHT DISTRIBUTION	Direct
POWER SUPPLY	48V / TRACK
WARRANTY	5 Years
FINISHING	Textured Black, Textured White
CONTROL	CASAMBI, DALI, ON/OFF

TECHNICAL DRAWING

LED FEATURES

LUMINOUS EFFICIENCY	UP TO 195 lm/W
CRI	CRI→90
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

ICONOGRAPHY

PROLINER L.G. AD. 48V EVO
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90

LENGTH	POWER	FINISHING	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
310	3.9	TB, TW	CS, DL, NF	60	741	653	3000K	5500XX.03U6.930.FI
310	3.9	TB, TW	CS, DL, NF	60	764	673	4000K	5500XX.03U6.940.FI
590	7.8	TB, TW	CS, DL, NF	60	1482	1305	3000K	5500XX.05U6.930.FI
590	7.8	TB, TW	CS, DL, NF	60	1529	1347	4000K	5500XX.05U6.940.FI
870	11.8	TB, TW	CS, DL, NF	60	2223	1958	3000K	5500XX.08U6.930.FI
870	11.8	TB, TW	CS, DL, NF	60	2293	2020	4000K	5500XX.08U6.940.FI

SELECT YOUR PREFERRED OPTION	CONTROL TYPE	XX	FINISHING	FI	BEAM ANGLE	BA
	CASAMBI	CS	Textured Black	TB	60°	60
	DALI	DL	Textured White	TW		
	ON/OFF	NF				

ACCESSORIES

	BT15E - Track 48V EVO	White	Black
	Track 48V EVO 1M	3080-0227E.WH	3080-0227E.BL
	Track 48V EVO 2M	3080-0228E.WH	3080-0228E.BL


	BT1E - Track 48V EVO	White	Black
	Track 48V EVO 1M	3080-0175E.WH	3080-0175E.BL
	Track 48V EVO 2M	3080-0176E.WH	3080-0176E.BL

	BT2E - Track 48V EVO	White	Black
	Track 48V EVO 1M	3080-0177E.WH	3080-0177E.BL
	Track 48V EVO 2M	3080-0178E.WH	3080-0178E.BL



TK18E - Track 48V EVO
Track 48V EVO 1M
Track 48V EVO 2M

White	Black
3080-0231E.WH	3080-0231E.BL
3080-0232E.WH	3080-0232E.BL



TK5E - Track 48V EVO
Track 48V EVO 1M
Track 48V EVO 2M

White	Black
3080-0250E.WH	3080-0250E.BL
3080-0251E.WH	3080-0251E.BL



TK9E - Track 48V EVO
Track 48V EVO 1M
Track 48V EVO 2M

White	Black
3080-0211E.WH	3080-0211E.BL
3080-0212E.WH	3080-0212E.BL