



DESCRIPTION

This track light was designed to provide high luminous performance in a small-sized fixture. Measuring only 55 mm in diameter, it incorporates a heatsink with excellent thermal conductivity. It is ideal for projects that require high levels of luminous quality, highlighting products or special spaces. The ROSS was specially developed for use with a low-voltage (48V) track adapter and is also available with an inTrack driver version for universal 3-circuit tracks (230V), as well as ceiling-mounted solutions in surface-mounted and recessed versions.

MOUNTING	Surface
LIGHT DISTRIBUTION	Direct
POWER SUPPLY	220-230V / 50-60 Hz
WARRANTY	5 Years
FINISHING	Textured Black, Textured White
CONTROL	CASAMBI, DALI / PUSH Dim, ON/OFF


LED FEATURES

LUMINOUS EFFICIENCY	UP TO 95 lm/W
CRI	CRI->90, CRI->97
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1

TECHNICAL DRAWING

ICONOGRAPHY

ROSS RECESSED SPOTLIGHT
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI->90

LENGTH	POWER	FINISHING	CONTROLTYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1637	1391	2700K	5460XX.12.927.FI
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1637	1391	2700K	5460XX.24.927.FI
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1637	1391	2700K	5460XX.36.927.FI
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1637	1391	2700K	5460XX.60.927.FI
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1671	1420	3000K	5460XX.12.930.FI
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1671	1420	3000K	5460XX.24.930.FI
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1671	1420	3000K	5460XX.36.930.FI
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1671	1420	3000K	5460XX.60.930.FI
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1785	1518	4000K	5460XX.12.940.FI
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1785	1518	4000K	5460XX.24.940.FI
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1785	1518	4000K	5460XX.36.940.FI
120	11,4	TB, TW	CS, DA, NF	12, 24, 36, 60	1785	1518	4000K	5460XX.60.940.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2052	1744	2700K	5451XX.12.927.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2052	1744	2700K	5451XX.24.927.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2052	1744	2700K	5451XX.36.927.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2052	1744	2700K	5451XX.60.927.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2185	1857	3000K	5451XX.12.930.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2185	1857	3000K	5451XX.24.930.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2185	1857	3000K	5451XX.36.930.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2185	1857	3000K	5451XX.60.930.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2300	1955	4000K	5451XX.12.940.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2300	1955	4000K	5451XX.24.940.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2300	1955	4000K	5451XX.36.940.FI
120	16,6	TB, TW	CS, DA, NF	12, 24, 36, 60	2300	1955	4000K	5451XX.60.940.FI

SELECT YOUR PREFERRED OPTION

CONTROLTYPE	XX	FINISHING	FI	BEAM ANGLE	BA
CASAMBI	CS	Textured Black	TB	12°	12
DALI / PUSH Dim	DA	Textured White	TW	24°	24
ON/OFF	NF			36°	36
				60°	60


ROSS RECESSED SPOTLIGHT
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI->97

LENGTH	POWER	FINISHING	CONTROLTYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1700	1445	2700K	5453XX.12.9727.FI
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1700	1445	2700K	5453XX.24.9727.FI
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1700	1445	2700K	5453XX.36.9727.FI
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1700	1445	2700K	5453XX.60.9727.FI
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1815	1542	3000K	5453XX.12.9730.FI
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1815	1542	3000K	5453XX.24.9730.FI
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1815	1542	3000K	5453XX.36.9730.FI
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1815	1542	3000K	5453XX.60.9730.FI
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1910	1624	4000K	5453XX.12.9740.FI
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1910	1624	4000K	5453XX.24.9740.FI
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1910	1624	4000K	5453XX.36.9740.FI
120	19,1	TB, TW	CS, DA, NF	12, 24, 36, 60	1910	1624	4000K	5453XX.60.9740.FI

 SELECT YOUR PREFERRED
 OPTION

CONTROLTYPE	XX	FINISHING	FI	BEAM ANGLE	BA
CASAMBI	CS	Textured Black	TB	12°	12
DALI / PUSH Dim	DA	Textured White	TW	24°	24
ON/OFF	NF			36°	36
				60°	60