



DESCRIPTION

Roxane is a cylindrical light fitting, composed of aluminium and textured white or black finish, which gives it a graceful and modern design. These aesthetic features and its high CRI, put this LED luminaire into the products category that can be included in any architectural project. Suspended or surface mounted, Roxane luminaire is easy to install and has a 24°, 36° or 60° beam angle.

MOUNTING TYPE	Surface
LIGHT DISTRIBUTION	Direct
WARRANTY	5 Years
FINISHING	Textured Black, Textured White
CONTROL	CASAMBI, DALI / Switch Dim, ON/OFF

LED FEATURES

LUMINOUS EFFICIENCY	UP TO 161 lm/W
CRI	CRI→90, CRI→97
LIFESPAN	50.000 Hours
STEPS MACADAM	3 Steps MacAdam
LUMEN MAINTENANCE	L90/B50
PHOTOBIOLOGICAL RISK	RG1


TECHNICAL DRAWING

ICONOGRAPHY

**ROXANE SURFACE SPOTLIGHT
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90**

LENGTH	POWER	FINISHING	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
140	8.1	TB, TW	CS, DA, NF	24, 36, 60	1211	1030	2700K	5332XX.BA.927.FI
140	8.1	TB, TW	CS, DA, NF	24, 36, 60	1244	1057	3000K	5332XX.BA.930.FI
140	8.1	TB, TW	CS, DA, NF	24, 36, 60	1300	1105	4000K	5332XX.BA.940.FI

SELECT YOUR PREFERRED
OPTION

CONTROL TYPE	XX	FINISHING	FI	BEAM ANGLE	BA
CASAMBI	CS	Textured Black	TB	24°	24
DALI / Switch Dim	DA	Textured White	TW	36°	36
ON/OFF	NF			60°	60


**ROXANE SURFACE SPOTLIGHT
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→97**

LENGTH	POWER	FINISHING	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
140	8.8	TB, TW	CS, DA, NF	24, 36, 60	918	780	2700K	5332XX.BA.9727.FI
140	8.8	TB, TW	CS, DA, NF	24, 36, 60	980	833	3000K	5332XX.BA.9730.FI
140	8.8	TB, TW	CS, DA, NF	24, 36, 60	1033	878	4000K	5332XX.BA.9740.FI

SELECT YOUR PREFERRED
OPTION

CONTROL TYPE	XX	FINISHING	FI	BEAM ANGLE	BA
CASAMBI	CS	Textured Black	TB	24°	24
DALI / Switch Dim	DA	Textured White	TW	36°	36
ON/OFF	NF			60°	60