. brilumen

SLIM WAVE OPAL INTERIOR

DESCRIPTION

The SLIM WAVE is presented with the LOW GLARE & OPAL or LOW GLARE & MICROPRISMATIC diffuser combination, emitting a high-quality light, thanks to the high Color Rendering Index (CRI->90) and a low level of glare, providing a pleasant and comfortable environment.

The SLIM WAVE is a luminaire that adapts perfectly to the needs and preferences of your project.

With about 3000lm, it is available in 3000K and 4000K color temperatures, three textured finishings, white, black, or silver, and offers a 5-year guarantee.

It's much more than just a luminaire - it's a statement of style and sophistication for any space.

MOUNTING TYPE LIGHT DISTRIBUTION POWER SUPPLY WARRANTY FINISHING

CONTROL

Suspension Direct 220-240V / 50-60 Hz 5 Years Textured Black, Textured black and white, Textured Silver, Textured White, Textured white and black DALI / Switch Dim, ON/OFF



TECHNICAL DRAWING

30,00





LUMINOUS EFFICIENCY CRI LIFESPAN STEPS MACADAM LUMEN MAINTENANCE PHOTOBIOLOGICAL RISK

ICONOGRAPHY



UP TO 152 lm/W CRI→90 50.000 Hours 3 Steps MacAdam L90/B50 RG1





SL SL

SLIM WAVE OPAL PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→90

				CONTRO					
1700	28	TB, TBW, TS, TW, TWB	3000K	DA,	NF	4039	29	44 170XX.1709	.930.FI
1700	28	TB, TBW, TS, TW, TWB	4000K	DA,	NF	4248	30	96 170XX.1709	.940.FI
	SELECT YOUR PREFERR		CONTRO		XX		СТ	FINISHING	
	OPTIO	OPTION		itch Dim	DA	3000K	30	Textured Black	TB
			0N/0)FF	NF	4000K	40	Textured black and white	TBW
								Textured Silver	TS
								Textured White	TW
								Textured white and black	TWB

ACCESSORIES

Q	Suspension Kit Suspension kit 1,5m (1un) Suspension kit 3 m (1un) Suspension kit 5 m (1un)	Silver 80303017.SL 80303018.SL 80303019.SL		
*	Ceiling Rose Recessed	Textured White	Textured Silver	Textured Black
	Ceiling Rose Recessed	80303020.TW	80303020.TS	80303020.TB
	Ceiling Rose Surface	Textured White	Textured Silver	Textured Black
	Ceiling Rose Surface	80303021.TW	80303021.TS	80303021.TB

1

. brilumen



 Power Cable 0,75
 ON/Off
 Dim Control

 Power Cable 1.5m
 80303001
 80303004

 Power Cable 3m
 80303002
 80303005

 Power Cable 5m
 80303003
 80303006