

DESCRIPTION

NOTICE: Product discontinued. Limited to existing stock. Please contact us!

Brilumen features a collection of versatile, modern and stylish wall light fittings and which, $depending \ on \ the \ design, \ beam \ angle \ and \ lumens, \ are \ suitable \ for \ different \ types \ of \ outdoor \ areas. \ If$ the goal is to light both up and down, Marley, Miller and Tosh are the best option, not forgetting that this last wall light has an optional reflector that allows you to close the beam angle. If you want to get a linear light line, the Wailer 16W is the right light fitting. However, if you are looking for a wall lighting to light a pathway, the recessed Levy 4W completes the goal efficiently. These products have an IP54 and are available in dark grey finish.

MOUNTING TYPE Surface LIGHT DISTRIBUTION Direct POWER SUPPLY 230 VAC / 50/60 Hz

WARRANTY 2 Years FINISHING TG CONTROL ON/OFF



LUMINOUS EFFICIENCY UP TO 86 lm/W CRI CRI→80 LIFESPAN 30000h Tp55 STEPS MACADAM 3 Steps MacAdam **LUMEN MAINTENANCE** L90/B50

PHOTOBIOLOGICAL RISK RG0

ICONOGRAPHY






















LENGTH	POWER	FINISHING	CONTROL TYPE	BEAM ANGLE	LED LUMENS	LUMINAIRE LM	COLOR TEMP.	CODE
108	16	TG	NF	20	1320	951	3000K	506.80.BA.30
108	16	TG	NF	20	1373	990	4000K	506.80.BA.40

SELECT YOUR PREFERRED OPTION ON/OFF NF



TECHNICAL DRAWING







108



PHOTOMETRIC DATA

POLAR DIAGRAM AND LUMINOUS FLUX - LENS Titulo





UDIE 37/11/1000N CDIBU 1130PMP